

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

5KG EVA HOT MELT ADHESIVE PELLETS UNFILLED IN YELLOW / TRANSLUCENT 280-30 SERIES BY JOWAT



Hot melt for automatic edgebanding suitable for solid wood, veneer, primed thermoplastic (PVC, ABS, PP), and resinated paper edgeband. Also used for softforming applications (especially designed for BAZ machines). Modern adhesive systems of the latest generation Furniture edges with "zero bondline" Hot melt adhesives for the current technologies For decades, edgebanding of wood-based panels with a variety of edgebands has been an established practice in the furniture industry. The quality demands concerning visual appeal, the technological progress in engineering, and also the almost unlimited diversity of materials to be processed all of these factors represent special challenges for the adhesive technology. In modern, high-quality furniture manufacture, the quality of the edgebanding is increasingly becoming a key criterion for evaluating the quality of the entire furniture item. The end customer demands a glueline that is hardly visible and perfect. Not least of all due to the development of ultramodern manufacturing methods, like laser or HotAir technologies, the industry has been talking about the so-called "zero bondline" for a long time. Jowat has met these challenges and offers modern and innovative solutions and they all lead to the "zero bondline". A milestone was the development of unfilled EVA hot melt adhesives for edgebanding, and this makes Jowatherm ® 280.30 a real standard classic. A modern improvement of the recent generation is Jowatherm ® 281.40, which has become established due to the excellent adhesion properties and the very wide processing window as very tolerant allrounder. Higher demands with regard to heat resistance can be met using hot melts based on polyolefin polymer. Suit:-



SKU	Option	Part #	Price
8704631		280-30 5KG	\$96

Model		
Туре	Hot Melt Adhesive - Pellets	
SKU	8704631	
Part Number	280-30 5KG	
Brand	Jowat	
Technical - Main		
Colour Name	Yellow / Translucent	
Feed Speed	10-40m/min.	
Material	EVA	
Processing Temperature [°C]	180-200	
Softening Range	Approx. 90 $\hat{A} \pm 5$ (Kofler bench)	
Dimensions		
Product Weight (Net Weight)	5 kg	
Country of Origin		
Manufactured in	Germany	
Packaging + Shipping		
Shipping Weight (Gross)	1.48 kg	



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 <u>hello@beyondtools.com</u>

Suit Virutex PEB250 Hot Melt Edgebander **Technical Data:-**Jowat EVA Hot Melt Adhesive 280.30/31 Data Sheet