



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## 13MM 750W ROTARY HAMMER BE 75-16 (600580190) BY METABO



SKU	Option	Part #	Price
8708217		600580190	\$439

Model	
Type	Rotary Hammer
SKU	8708217
Part Number	600580190
Barcode	4007430203953
Brand	Metabo
Technical - Main	
Motor Speed - No Load	0 - 660 rpm
Dimensions	
Product Weight (Net Weight)	2.6 kg
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

Robust die cast aluminium gear housing for optimum heat dissipation and durability

Rotating carbon brush bridge for maximum performance even in anti-clockwise operation, e.g. for the removal of stubborn screws

Vario (V)-Electronics for working at customised speeds to suit various application materials

Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly

Spindle with hexagonal recess for screwdriver bits for working without chuck

Suitable for powerful drilling of larger diameters and for stirring thick, liquid-like materials

The machine shown may differ in equipment and technical details depending on the configuration. **Specifications:**

Rated input power: 750 W

Output power: 470 W

Drill Å~ steel: 16 mm / 5/8 "

Drill-Å~ soft wood: 50 mm / 2 "

No-load speed: 0 - 660 rpm

Revolutions at rated load: 350 rpm

Gears: 1

Maximum torque: 75 Nm / 664 in-lbs

Collar diameter: 43 mm / 1 11/16 "

Chuck capacity: 1.5 - 13 mm // 1/16 - 1/2 "

Drill spindle with hexagonal recess: 6.35 mm / 1/4 "

Drill spindle thread: 1/2 " - 20 UNF

Weight (without power cable): 2.6 kg / 5.7 lbs kg

Cable length: 2.5 m / 8 ft

**Vibration:**



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Drilling in metal: 2.5 m/s<sup>2</sup>

Uncertainty of measurement K: 1.5 m/s<sup>2</sup>

**Noise Emissions:**

Sound pressure level: 81 dB(A)

Sound power level (LwA): 92 dB(A)

Uncertainty of measurement K: 3 dB(A)

**Includes:**

Geared chuck

Chuck key

Long side handle