



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## BSW BOTTOMING HSS TAP BY BORDO



SKU	Option	Part #	Price
8709100	Size: 1/2" x 12TPI	3028-1/2B	\$33.3
9803119	Size: 1/4" x 20TPI	3028-1/4B	\$15.6
9803117	Size: 3/16" x 24TPI	3028-3/16B	\$15.6
9803124	Size: 3/8" x 16TPI	3028-3/8B	\$22.9
9803122	Size: 5/16" x 18TPI	3028-5/16B	\$16.64
9803114	Size: 5/32" x 32TPI	3028-5/32B	\$25
8729443	Size: 7/16" x 18TPI	3030-7/16B	\$36.4

Model	
Type	Bottoming Tap
SKU	8709100
Part Number	3028-1/2B
Barcode	9326518030744
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



### About this product:

HSS BSW Bottoming Hand and Machine Tap.

British Standard Whitworth has a thread angle of 55 degrees as opposed to 60 degrees in Metric and Unified threads.

This thread form was developed by Sir Joseph Whitworth in 1841.

The thread form has rounded roots and crests and is specified in BS84:1956.

Bottoming Taps have a lead of two threads and are used to ensure minimum thread run-out when tapping to the bottom



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

of a blind hole.

Bottoming Taps are typically preceded by the use of a Taper or Intermediate Tap.

Manufactured from HSS this general purpose tap is designed for use in medium tensile materials and is for hand or general machine use.