

UNC INTERMEDIATE HSS TAP BY BORDO



SKU	Option	Part #	Price
8709113	Size: 1" x 8TPI	3032-1I	\$104
8709104	Size: 1/2" x 13TPI	3032-1/2I	\$34.8
8709107	Size: 1/4" x 20TPI	3032-1/4I	\$16.95
8709110	Size: 10G x 24TPI	3032-10GI	\$16.95
8709116	Size: 3/16" x 24TPI	3032-3/16I	\$17.7
8709119	Size: 3/4" x 10TPI	3032-3/4I	\$62.4
8709122	Size: 3/8" x 16TPI	3032-3/8I	\$23.8
8709129	Size: 5/16" x 18TPI	3032-5/16I	\$16.95
8709132	Size: 5/8" x 11TPI	3032-5/8I	\$43.95
8709135	Size: 7/16" x 14TPI	3032-7/16I	\$28.95
8709138	Size: 8G x 32TPI	3032-8GI	\$19.5
8709141	Size: 9/16" x 12TPI	3032-9/16I	\$42.64

Model	
Type	Intermediate Tap
SKU	8709138
Part Number	3032-8GI
Barcode	9326518026983
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg

HSS UNC Intermediate Hand and Machine Tap.

Unified National Coarse thread form was introduced in 1948 as an attempt to standardise thread forms in the USA, Canada and the UK.

The thread profile of UNC is the same as for metric threads and is described in the JIS B0206 standard.

The thread is described by its major diameter and the number of threads per inch of length (TPI).

This thread series is commonly used in the mass production of bolts, screws and nuts.

It is used for threading into lower tensile strength materials (bronze, brass, aluminium and plastics) to obtain the best



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

resistance to stripping of the internal thread.

It is also used on quick assembly or disassembly or if corrosion or slight damage is possible.

Intermediate Taps have a lead of four threads and are used in most general purpose applications to cut a thread true to a pre-drilled pilot hole.

Manufactured from HSS this general purpose tap is designed for use in medium tensile materials and is for hand or general machine use.

Options

3032-1I

3032-1/2I

3032-8GI

3032-10GI

3032-3/16I

3032-1/4I

3032-3/4I

3032-3/8I

3032-7/16I

3032-5/8I

3032-5/16I

3032-9/16I