

## UNF TAPER HSS TAP BY BORDO



SKU	Option	Part #	Price
8709155	Size: 1" X 12TPI	3034-1T	\$113
8709145	Size: 1/2" X 20TPI	3034-1/2T	\$35
8709148	Size: 1/4" X 28TPI	3034-1/4T	\$15.9
8709152	Size: 10G X 32TPI	3034-10GT	\$15.6
8709179	Size: 3/16" X 32TPI	3036-3/16T	\$21.84
8709158	Size: 3/4" X 16TPI	3034-3/4T	\$57.2
8709161	Size: 3/8" X 24TPI	3034-3/8T	\$20.8
8709164	Size: 5/16" X 24TPI	3034-5/16T	\$15.6
8709167	Size: 5/8" X 18TPI	3034-5/8T	\$54.7
87809170	Size: 7/16" X 20TPI		\$
8709559	Size: 7/8" X 14TPI	3034-7/8T	\$110
8709173	Size: 8G X 36TPI	3034-8GT	\$17.7
8709176	Size: 9/16" X 18TPI	3034-9/16T	\$42.64

Model	
Type	Taper Tap
SKU	8709173
Part Number	3034-8GT
Barcode	9326518027522
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg

### About this product:

HSS UNF Taper Hand and Machine Tap.

Unified National Fine thread form was introduced in 1948 as an attempt to standardise thread forms in the USA, Canada and the UK.

The thread profile of UNF is the same as for metric threads and is described in the JIS B0206 standard.

The thread is described by its major diameter and the number of threads per inch of length (TPI).

When used on external threads this series has greater tensile stress area than coarse threads of the same size.

Fine series threads will resist stripping out better than coarse threads in areas where the external and mating internal



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

threads are subjected to loads equal to or greater than the capacity of the screw or bolt.

Fine threads are also used where the length of engagement is limited 1-1/4 or where wall thickness demands a fine pitch.

Taper Taps have a lead of eight threads and are used as a starting tap in difficult or high precision holes.

Manufactured from HSS this general purpose tap is designed for use in medium tensile materials and is for hand or general machine use.

**Options**

3034-1T

3034-1/2T

3034-10GT

3034-1/4T

3034-8GT

3034-3/4T

3036-3/16T

3034-5/16T

3034-9/16T

3034-7/8T

3034-5/8T

3034-3/8T