



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## MC TAPER CHROME TAP BY BORDO



SKU	Option	Part #	Price
8707154	Size: 12mm x 1.75mm	4220-12.00T	\$13.52
8200145	Size: 14mm x 2.0mm	4221-14.00T	\$18.72
8709842	Size: 2mm x 0.4mm	4220-2.00T	\$7.3
46303	Size: 3mm x 0.5mm	4220-3.00T	\$11.44
8710533	Size: 5mm x 0.8mm	4220-5.00T	\$8.32
8710535	Size: 6mm x 1mm	4220-6.00T	\$8.32
8710537	Size: 8mm x 1.25mm	4220-8.00T	\$8.32

Model	
Type	Taper Tap
SKU	8709842
Part Number	4220-2.00T
Barcode	9326518040774
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)



**About this item:**

Chrome Alloy Metric Coarse Taper Hand Tap.



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Used as thread chasers to clean an existing thread.

They can also be used to create a new female thread in non-ferrous metals and plastics.

Chrome alloy taps are not suitable for creating precision, safety or critical threads.

Metric Coarse angle of thread is 60 degrees.

The crest is flat and the thread has clearance at the root allowing external thread and internal thread to engage well.

Larger root radius and lower thread height enable easy screw thread processing and increase thread screw strength.

The major diameter of external thread and pitch are specified by a simple numerical value (most commonly measured in millimetres).

Taper Taps have a lead of eight threads and are used as a starting tap in difficult or high precision holes.

**Options**

4220-3.00T

4220-2.00T

4220-5.00T

4220-8.00T

4220-12.00T

4221-14.00T

4220-6.00T