



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## 19/64" HSS COBALT LEFT HAND DRILL 2005-19/64 BY BORDO



SKU	Option	Part #	Price
8710543		2005-19/64	\$12

Model	
SKU	8710543
Part Number	2005-19/64
Barcode	9326518003892
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg

### BORDO FRACTIONAL LEFT HAND COBALT TOUGH HSS-Co5 JOBBER DRILLS ANSI B94-11135° Split Point

(crankshaft point) Split point is self centering and the short distance from the drill axis to the outer corners results in faster penetration, reducing the need for end thrust. The 135° point should be used to cut harder steel materials especially in deep hole applications. In these situations it will produce thicker chips minimising work hardening of the cavity. Faster penetration reduces abrasion and friction along the cutting edges. Cobalt HSS jobber drills are extremely hard and provide superior performance and increased tool life especially in stainless steel and high tensile steel.

**USAGE** Left Hand jobber drills are ideal for use with screw extractors to remove broken bolts and screws. **DRILL BIT SURFACE TREATMENT** Bronze Finish (gold oxide). The metallic brown coloured low temperature temper treatment is normally only used on cobalt tools for identification purposes.

**Specifications:**

Spindle Speed Stainless Steel RPM:608

Spindle Speed Tool Steel RPM:912

Spindle Speed Cast Iron RPM:1217

Spindle Speed Malleable Iron RPM:1369

Spindle Speed Med. Carbon Steel RPM:1521

Spindle Speed Free Cutting Steel RPM:2180

Spindle Speed Aluminium/Brass RPM: 3092

Spindle Speed Wood/Plastic RPM:4613

Feed per revolution mm: 0.2