


## 800W SDS PLUS COMBINATION HAMMER KHE3251 (600659190) BY METABO



SKU	Option	Part #	Price
8712780		600659190	\$659

Model	
Type	Rotary Hammer
SKU	8712780
Part Number	600659190
Barcode	4007430214386
Brand	Metabo
Dimensions	
Product Weight (Net Weight)	3.6 kg
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

**Description:**

Combination hammer with 3 functions: hammer drilling, drilling and chiselling

Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for drilling in wood and metal

Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health

Ergonomic housing shape for chiselling tasks without side handle

Vario (V)-Electronics for working at customised speeds to suit various application materials

Metabo Marathon-motor with dust protection for long service life

High performance hammer action, precisely mounted in a housing made of aluminium alloy: long-lasting and robust  
Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly  
Cable-protecting ball joint for optimal freedom of motion when working

**Specifications:**

Max. single blow energy (EPTA): 3.1 J

Maximum impact rate: 4470 bpm

Rated input power: 800 W

Drill-Ã~ concrete with hammer drills: 32 mm / 1 1/4 " mm

Drill-Ã~ masonry with core bits: 82 mm / 3 1/4 "



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Drill ~ steel: 13 mm / 1/2 "

Drill-~ soft wood: 35 mm / 1 3/8 "

No-load speed: 0 - 1150 rpm

Revolutions at rated load: 920 rpm

Bit retainer: SDS-plus

Collar diameter: 50 mm / 1 31/32 " mm

Weight (without power cable): 3.6 kg / 7.9 lbs kg

Cable length: 4 m / 13 ft

**Vibration:**

Hammer drilling concrete: 12.9 m/s <sup>2</sup>

Uncertainty of measurement K: 1.5 m/s <sup>2</sup>

Chiseling: 10.9 m/s <sup>2</sup>

Uncertainty of measurement K: 1.5 m/s <sup>2</sup>

**Noise Emission:**

Sound pressure level: 91 dB(A)

Sound power level (LwA): 102 dB(A)

Uncertainty of measurement K: 3 dB(A)

**Includes:**

Hammer chuck for tools with SDS-plus shank end

Keyless chuck for tools with cylindrical shank

Metabo VibraTech (MVT) side handle

Drilling depth guide

Plastic carry case