

## 950W DIE GRINDER GE950G (600618190) BY METABO



SKU	Option	Part #	Price
8713026		600618190	\$719

Model	
Type	Die Grinder
SKU	8713026
Part Number	600618190
Barcode	4007430212429
Brand	Metabo
Technical - Main	
Motor Speed - No Load	2500 - 8700 rpm
Dimensions	
Product Weight (Net Weight)	1.7 kg
Features	
Standard Inclusions	Collet 1/4"
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

### Features:

High torque and compact design thanks to robust planetary gear

Spindle lock for simple change of tools

Aluminium die-cast bearing flange for long service life of the machine

Vario-Constamatic (VC)- Electronics for work with materials requiring customised speeds, which remain almost constant under load

Thumbwheel for Speed Preselection

Electronic safety shutdown of the motor for safe working in case the tool stops unexpectedly

Restart protection: prevents unintentional start-up after power supply interruption

Electronic overload protection for long service life

Precise collar for stationary use

Removable protective rubber cap for comfortable and safe working

Slim design for ideal handling

Precision collet for precise concentricity

Metabo Marathon motor with patented dust protection for long service life

The specialist: handy grinder with especially high torque; ideal for grinding inner and outer surfaces in combination with flap wheels (see Accessories)

### Specifications:

No-load speed: 2500 - 8700 rpm

Rated input power: 950 W

Output power: 510 W

Revolutions at rated load: 7200 rpm

Collar diameter: 43 mm / 1 11/16 "

Collet chuck bore: 6 mm / 0.2362 "

Weight (without power cable): 1.7 kg / 3.7 lbs



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Cable length: 4 m / 13 ft

**Vibration**

Surface grinding (up to  $\bar{A}$  25 mm): 2.5 m/s<sup>2</sup>

Surface grinding (up to  $\bar{A}$  50 mm): 2.5 m/s<sup>2</sup>

Uncertainty of measurement K: 1.5 m/s<sup>2</sup>

**Noise emission**

Sound pressure level: 87 dB(A)

Sound power level (LwA): 98 dB(A)

Uncertainty of measurement K: 3 dB(A)

**Includes:**

Collet 6 mm

Collet 1/4"

Protective rubber cap

Side handle

1 open-jawed spanner