

20,000KG AIR / HYDRAULIC BOTTLE JACK 2026T BY TRADEQUIP PROFESSIONAL



SKU	Option	Part #	Price
8713259		2026T	\$299

Model	
Type	Bottle Jacks
SKU	8713259
Part Number	2026T
Barcode	9332105002261
Brand	Tradequip
Size	20000kg
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

Our **Tradequip "Made for the Trade"** Air/Manual 20,000kg Bottle Jack is designed to operate either manually or pneumatically. The manual function allows for normal operation anywhere, even without an air supply. Ideal for onsite/offsite lifting of farm vehicles, heavy duty machinery, industrial construction equipment and more. The Air/Manual Bottle Jack is equipped with an hydraulic system and a mounted powerful manual pump. Used on light or heavy vehicles, they are compact, versatile and safe to use. Our **Tradequip "Made for the Trade"** design includes a quality safety valve to prevent overloading and a larger base to provide high safety and greater stability. This Air/Manual Bottle Jack is fitted with a Professional Quality Air Turbo Motor designed to meet the demands of adverse climate conditions and extreme temperatures. This 'Best Selling' Jack is a favourite of the Qld and WA mine maintenance crews, due to it's strong lifting power and long lasting wear characteristics. This 20,000kg heavy-duty air/hydraulic bottle jack is the perfect choice for a wide variety of uses. The power of air



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

makes it easy to lift farm vehicles, trucks, trailers, heavy equipment and other large loads! Use this workhorse with a 90-120 PSI rated air pressure supply to lighten the load and provide the fast, strong lifting power you need, or operate it manually for normal operation just about anywhere. The 265-430mm lift range raises the load to the desired height and a knurled, heat-treated pad with 100mm screw height adjustment allows you to fine-tune the jack from there.

Fitted with a safety overload valve for extra protection, so that even if the jack gets loaded up with too much weight, the safety overload kicks in and gently lowers the unit before the operator is put in a dangerous situation. Designed for durability, the rugged high-grade steel frame is teamed with a lead-free paint finish that covers the entire surface to ensure long-lasting wear and help prevent rust. The paint is oil, grease and dirt-resistant for easy cleanup no matter how often you put it to work.

Always consider the TradeQuip Air Turbo Motor

Features:

Best practise quality controlled manufacturing process

CNC machined cast alloy piston and barrel

Barrel is hardness rated opposed to other mild steel variations

Piston & Barrel combination present longlife wear characteristics similar to an engine crank and bearing

Duro70 rated nitrile O'rings (best for air tool applications)

provide good elasticity and friction rating

Results in longer duty cycle over adverse Australian climate and temperature ranges

Superior lithium grease lubrication is less prone to drying or flushing out from wet ,dry, hot or cold air supplies

Lithium grease re-emulsifies when a few drops of air tool oil or 32 grade hydraulic oil is regularly added

Specifications:

Safe Working Capacity: 20,000kg

Minimum Height: 265mm

Maximum Height: 430mm

Hydraulic Lift: 185mm

Adjustable Height: 100mm

Base Area: 224x134mm

Work Pressure: 90-120psi

Carton: 290 x 200 x 290mm

Weight: 16kg

IMPORTANT: NEVER get beneath a vehicle that is only supported by a jack. ALWAYS chock the vehicle wheels and use support stands.