

## 254MM 2000W TABLE SAW TS254 BY METABO



SKU	Option	Part #	Price
8713367		600668190	\$1189

Model	
Type	Table Saw
SKU	8713367
Part Number	600668190
Barcode	4007430229830
Brand	Metabo
Dimensions	
Product Length	740 mm
Product Width	750 mm
Product Height	355 mm
Product Weight (Net Weight)	33.4 kg
Packaging + Shipping	
Shipping Weight (Gross)	33.4 kg

### Features:

Very compact with folded stand for comfortable transport and space-saving storage

Anti-twist tubular frame construction for highest demands on the building site and during installations

Cables and all add-on components for transport can be stored at the casing

Powerful motor with electronic overload protection

Motor brake for quick stop of the saw blade in 3 seconds

Restart protection: prevents unintentional startup after power cut

Soft start for long service life of motor and drive

Precise parallel guide with double clamping and quick fastening

Precise saw blade inclination via gear guide

Automatic resetting to 0 ° after undercuts

Easy saw blade change with spindle lock

Splitting wedge can be lowered without tools for hidden cuts and transport

Precise, extendable table width extension for extra large working surfaces

Second working height for working near ground level

Dual port dust extraction for low dust working

### Includes:

Carbide circular saw blade with alternately bevel-ground tooth (40 teeth)

Stand

Hard rubber tyres

Parallel guide/ripping dence

Mitre guide

Table length extension

Table width extension (right)

Saw blade case



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Chip and dust extraction unit

Rubber cable (3 m)

Push stick

<b>Dimensions</b>	740 x 750 x 355 mm
<b>Support surface</b>	970 x 995 mm
<b>Working height</b>	850/355 mm
<b>Cutting height</b>	0 - 87 mm
<b>Maximum cutting height 90/45 °</b>	87 mm/50 mm
<b>Maximum cutting width at parallel guide/rip fence</b>	630 mm
<b>Maximum material width at mitre fence</b>	200 mm
<b>No-Load Speed</b>	4.200 /min
<b>Max. cutting speed</b>	56/184 m/s
<b>Saw blade</b>	~ 254 x 30 mm
<b>Saw blade swivel range</b>	-1,5 - 46,5 °
<b>Rated input power</b>	2 kW
<b>Output power</b>	1,27 kW
<b>Weight</b>	33,4 kg
<b>Cable length</b>	3,1 m