

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

## 254MM (10") TABLE SAW DWE7491-XE BY DEWALT





## Features

26.6 kg unit weight and optimised footprint make this the most portable saw in its class

Steel roll cage protects saw against jobsite drops and impacts Rack and pinion fence system, front and rear fence lock and large, clear scales combine to give an extremely accurate and easy to use saw

Powerful 2000 Watt motor for high performance in all applications (1700 Watt 110V version UK only) Fence system provides 825 mm of rip capacity in a portable design for cutting large sheet materials to size Cast table top design ensures accuracy and precision Quick bevel lock with large scale for easy, accurate adjustments.

## Specifications

Power Input: 2000 Watts Blade Speed: 3800 rpm Blade Diameter: 254 mm Blade Bore: 30 mm Bevel Capacity: -3 to 48 ° Max. Ripping Capacity [right]: 825 mm Max. Ripping Capacity [left]: 558 mm Max. Depth of Cut at 90 °: 77 mm Max. Depth of Cut at 45 °: 57 mm Table Size: 670x630 mm Sound Power: 106 dB(A) Sound Power Uncertainty: 3.3 dB(A) Sound Pressure: 95 dB(A)



| SKU                            | Option | Part #     |  | Price  |
|--------------------------------|--------|------------|--|--------|
| 8716356                        |        | DWE7491-XE |  | \$1310 |
|                                |        |            |  |        |
| Model                          |        |            |  |        |
| Туре                           |        |            | Table Saw  |        |
| SKU                            |        |            | 8716356  |        |
| Part Number                    |        |            | DWE7491-XE   |        |
| Barcode                        |        |            | 5035048448465  |        |
| Brand                          |        |            | Dewalt   |        |
| Size                           |        |            | 250mm (10")  |        |
| Technical - Main               |        |            |  |        |
| Power Source                   |        |            | 240V 50Hz Single Phase   |        |
| Technical - Saw                |        |            |  |        |
| Rip Capacity                   |        |            | 825 mm   |        |
| Blade (Main) - Bore Size (mm)  |        |            | 30mm   |        |
| Blade (Main) - Diameter (Max.) |        |            | 250 mm   |        |
| Dimensions                     |        |            |  |        |
| Product Length                 |        |            | 577 mm   |        |
| Product Width                  |        |            | 742 mm   |        |
| Product Height                 |        |            | 475 mm   |        |
| Product Weight (Net Weight)    |        |            | 26.6 kg  |        |
| Features                       |        |            |  |        |
| Push Stick Included            |        |            | ✓  |        |
| Standard Inclusions            |        |            | Mitre fence, Dust port reducer,<br>Push stick, 2 blade spanners,<br>Parallel fence, 24 tooth SERIES<br>30® saw blade |        |
| Safety                         |        |            |  |        |
| Blade Guard                    |        |            | ✓  |        |
| Workshop (Site) I              | nfo    |            |  |        |
| Electrical Connection          |        |            | 10Amp Plug & Lead  |        |
| Packaging + Ship               | ping   |            |  |        |
| Shipping Weight (Gross)        |        |            | 26.5 kg  |        |
| Shipping Notes                 |        |            | This product is classified as<br>'Heavy / Oversized' and<br>generally does not qualify for<br>FREE SHIPPING.         |        |



## 23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 <u>hello@beyondtools.com</u>

Sound Pressure Uncertainty: 3 dB(A) Please note stands shown pictured are not included unless part of a bonus offer - limited stock, enquire within\*