

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

125MM 900W ANGLE GRINDER W9-125 QUICK (600374000) BY METABO





Low fatigue as never before: compact angle grinder with smallest handle circumference in its class for perfect ergonomics

Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque

Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System

Tool-free adjustable guard; twist-proof

Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress Restart protection after power interruption Gear housing can be unscrewed, rotated in 90 ° steps and

remounted for left-handed operation or cutting Auto-stop carbon brushes to protect the motor The machine shown may differ in equipment and technical details depending on the configuration.

Specifications:

Grinding wheel Ã[°]: 125 mm / 5 " Rated input power: 900 W Output power: 550 W No-load speed: 10500 rpm Revolutions at rated load: 7500 rpm Torque: 2.5 Nm / 22 in-lbs Spindle thread: M 14 Weight (without power cable): 2.1 kg / 4.6 lbs Cable length: 4 m / 13 ft **Vibration:** Surface grinding: 6 m/s ²



SKU	Option	Part #		Price
8716817		600374000		\$299
Model				
Туре			Angle Grinder	
SKU			8716817	
Part Number			600374000	
Barcode			4007430240989	
Brand			Metabo	
Technical - Main				
Motor Speed - No Load			10500 rpm	
Dimensions				
Product Weight (Net Weight)			2.1 kg	
Packaging + Ship	ping			
Shipping Weight (Gross)			2.1 kg	



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 <u>hello@beyondtools.com</u>

Uncertainty of measurement K: 1.5 m/s ² Grinding with sandpaper: 2.5 m/s ² Uncertainty of measurement K: 1.5 m/s ² **Noise emission:** Sound pressure level: 93 dB(A) Sound power level (LwA): 104 dB(A) Uncertainty of measurement K: 3 dB(A) **Includes:** Guard Inner Support Flange M-Quick flange nut

Side handle

WWW.BEYONDTOOLS.COM - © COPYRIGHT 2024 BEYOND TOOLS - VERSION: 20240502