



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

TORQUE WRENCH ADJUSTABLE CLICK WRENCH WITH MARKED SCALE AND FIXED RATCHET HEAD SERIES 7455 BY BAHCO



SKU	Option	Part #	Price
8717385	Size: 1-5Nm 1/4" Drive - 7455-5	7455-5	\$197.8
8731296	Size: 12-60Nm 3/8" Drive - 7455-60	7455-60	\$723.8
8731299	Size: 160-800Nm 3/4" Drive - 7455-800	7455-800	\$832.9
8717384	Size: 20-100Nm 3/8" Drive - 7455-100	7455-100	\$275.2
8731300	Size: 200-1000Nm 1" Drive - 7455-1000	7455-1000	\$1599
8731294	Size: 4-20Nm 1/4" Drive - 7455-20	7455-20	\$670
8717386	Size: 40-200Nm 1/2" Drive - 7455-200	7455-200	\$390.9
8731295	Size: 5-25Nm 1/4" Drive - 7455-25	7455-25	\$226.9
8731297	Size: 60-300Nm 1/2" Drive - 7455-300	7455-300	\$373.2
8731298	Size: 68-340Nm 1/2" Drive - 7455-340	7455-340	\$591.4



Model	
Type	Torque Wrench
SKU	8717385
Part Number	7455-5
Barcode	7314150119639
Brand	Bahco
Country of Origin	
Manufactured in	USA
Warranty	
Warranty	Limited Lifetime
Packaging + Shipping	
Shipping Weight (Gross)	6.123 kg

Features:-

- Dual scales in N·m/ft.lb and N·m/in.lb (sizes 5-25 N·m)
- Range covering between 1 and 1,000 N·m /11 in.lb and 701 ft.lb torque values
- Can be used clockwise or anticlockwise
- Controlled torque application events to $\pm 4\%$ CW and ACW
- Clicking system triggers a tactile and audible signal
- Fixed ratchet heads with 24-36 teeth from 1/4" to 1" square drives (1/4" to 1/2" with quick release)
- All-metal rugged, durable wrench with sealed mechanism
- Anti-slip knurled metal handle resistant to impact, pressure and chemicals
- Sizes 5 to 340 N·m come in a semi-transparent tube with eurohole
- Sizes above in plastic blow mould case
- All wrenches come with a factory declaration of conformity according to ISO 6789-1:2017
- Made in USA

Specification:-

Product	range	range	range	range	A	B	C	D	E	F	Weight
7455-5	1-5 Nm	11-45 ft.lb	1/4"	0.07 Nm	0.8 Nm	250 mm	250 mm	27 mm	24 mm	16 mm	0.280 kg
7455-20	4-20 Nm	40-175 ft.lb	1/4"	0.1 Nm	0.20 Nm	250 mm	250 mm	27 mm	24 mm	16 mm	0.280 kg
7455-25	5-25 Nm	40-210 ft.lb	1/4"	0.1 Nm	0.40 Nm	250 mm	275 mm	27 mm	24 mm	16 mm	0.280 kg
7455-100	12-60 Nm		3/8"	0.1 Nm	0.1 Nm	300 mm	375 mm	30 mm	26 mm	20 mm	1.150 kg
7455-1000	200-1000 Nm		1"	0.1 Nm	0.1 Nm	400 mm	300 mm	30 mm	26 mm	20 mm	1.170 kg
7455-100	40-200 Nm		1/2"	2 Nm	1.5 Nm	400 mm	400 mm	40 mm	41 mm	26 mm	1.400 kg
7455-200	40-200 Nm		1/2"	2 Nm	1.5 Nm	400 mm	400 mm	40 mm	41 mm	26 mm	1.400 kg
7455-300	60-300 Nm		1/2"	2 Nm	1.5 Nm	410 mm	380 mm	40 mm	41 mm	26 mm	1.400 kg
7455-340	68-340 Nm		1/2"	2 Nm	1.5 Nm	380 mm	380 mm	40 mm	41 mm	26 mm	1.400 kg
7455-800	160-800 Nm		3/4"	5 Nm	2.7 Nm	500 mm	400 mm	50 mm	50 mm	28 mm	2.500 kg
7455-1000	200-1000 Nm		1"	10 Nm	5.0 Nm	500 mm	470 mm	50 mm	50 mm	28 mm	2.500 kg



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Options

7455-5

7455-100

7455-25

7455-200

7455-1000

7455-60

7455-300

7455-340

7455-800

7455-20