



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

18V 5.0AH BRUSHLESS 2 SPEED FRAMING NAILER KIT DCN692P2 BY DEWALT



SKU	Option	Part #	Price
8717492		DCN692P2-XE	\$899

Model	
Type	Nailer
SKU	8717492
Part Number	DCN692P2-XE
Barcode	5035048467787
Brand	Dewalt
Technical - Main	
Battery Voltage (V)	18V
Brushless Motor	✓
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

Features:

18V XR Li-Ion Two Speed Framing Nailer featuring BRUSHLESS motor technology
Two speeds - or power levels - to optimise the nailer for firing all lengths of nails
Benefit from longer runtime, quicker readiness to fire, less recoil and more durability when firing short nails
BRUSHLESS motor technology offers the power to fire a 90mm Ring Shank nail in Soft Wood and 63mm into Hard Woods
The sequential operating mode allows for precision placement and the bump operating mode provides the user with production speed
Mechanical rather than gas operation offers constant performance at temperature between -20 and 50 degrees celcius and minimal cleaning/service requirements
Class leading vibration and sound figures, offer fantastic user protection
Versatile 30 - 34 degree magazine angle will accept most clipped head, and off centre round head paper tape or wire weld collated framing nails
Reversible belt/rafter hook provides increased portability and versatility on the job-site
Depths can be easily adjusted using the thumb wheel depth adjuster
Increased visibility and durability along with protection for work-surface from the non-mar contact-trip
Ergonomic tool design allows the nailer to fit easily between a 400mm centre stud
Gas free operation offers a significant saving in running costs
Tool free stall/jam clearance minimises user down time



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Cordless design allows you to work without the inconvenience and safety risk of trailing leads
User can engage contact trip lock-off and prevent accidental dis-charge of fastener
Dry fire lockout ensures that the tool is protected from firing without nails in the magazine

Specifications:

Nail Diameter: 2.8 - 3.3 mm

Magazine angle: 30 - 34 °

Magazine loading: Rear - load

Nail Length: 50 - 90 mm

Magazine capacity: Up to 55 Nails

Trigger Type: Bump & Sequential

Nailer Operating Mode: Selective

Integrated Belt Hook: Yes

Jam Clearing: Yes

Temperature Range: -20 to 50 °C

Includes:

2 x 5.0Ah XR Li-Ion battery packs with state of charge indicator

Multi-voltage XR charger

Reversible belt hook

Non-mar tip

Heavy duty carrying case