

18V BRUSHLESS COLLATED DRYWALL SCREWDRIVER BARE (TOOL ONLY) DCF620KN-XE BY DEWALT



SKU	Option	Part #	Price
8718399		DCF620KN-XE	\$385

Model	
Type	Screwdriver
SKU	8718399
Part Number	DCF620KN-XE
Barcode	5035048548103
Brand	Dewalt
Packaging + Shipping	
Shipping Weight (Gross)	1.88 kg

Features:-

18V XR Li-Ion BRUSHLESS Drywall Screwdriver for efficient fitting of drywall

Powerful 4400rpm BRUSHLESS motor drives screws efficiently and effectively offering maximum runtime and a compact tool

One of the lightest and most compact tools on the market - it ensures that you can work comfortably and get into small spaces

Quick release collated screw magazine accepts most collated screws to allow the user to fit boards more quickly

Easy collated screw magazine opening to allow for quick cleaning of drywall dust

Tool free depth control and fine depth control for simple but effective setting

Collated screw magazine rotates on tool without removal to allow the operate in corners with the minimum of fuss

LED worklight offers valuable light when working in small spaces or areas with limited light

5.0Ah High Capacity battery pack coupled with the BRUSHLESS motor offers eXtreme Runtime and compatability with the rest of your 18V XR tools

Trigger lock on lets you work without having to pull the trigger

Ergonomically designed rubber grip gives you excellent user comfort whilst using the tool in either the "in-line" or "pistol-grip" hand position

Also supplied with locking nose cone so that you can work with the same tool on sites where collated drywall screws are not supplied

"Set and forget" feature remembers your fine depth adjustment setting when removing and replacing the nose cone

Robust and durable design means that the tool is jobsite tough

Angled belt hook can be positioned for left or right handed users and fixes tool strongly onto tool belt / pouch



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Supplied with TSTAK 2 kitbox to interconnect with all of the rest of your TSTAK storage system

Specifications:-

Voltage: 18 V

Battery Capacity: 5.0 Ah

Tool Holder (Hex): 6.35 mm

Power Output: 435 Watts

No Load Speed: 0 - 4400 rpm

Max Torque: 5 - 30 Nm

Weight: 1.88 kg

Length: 380 mm

Height: 233 mm

Hand/Arm Vibration: <2.5 m/s²

Uncertainty K 1 (Vibration): 1.5 m/s²

Sound Pressure: 77 dB(A)

Uncertainty K 1 (Sound): 3 dB(A)

Acoustic Pressure: 88 dB(A)

Uncertainty K 2 (Sound): 3 dB(A)

Battery chemistry: Li-Ion

Head Length: 335 mm

Includes:-

DCF6201 - collated screw magazine

DT7205-QZ - PR2 collated screw bit

Single Screw Nose cone

DT7520-QZ - Magnetic bit extender with 25mm PR2 screw bit