



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

STI MC TAPER HSS TAP BY BORDO



SKU	Option	Part #	Price
8719059	Size: 5mm x 0.8mm	3520-5.00T	\$44.72
8719061	Size: 6mm x 1.0mm	3520-6.00T	\$44.72
8719063	Size: 8mm x 1.25mm	3520-8.00T	\$52

Model	
Type	Taper Tap
SKU	8719059
Part Number	3520-5.00T
Barcode	9326518071853
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg

Metric Coarse.

HSS Hand and Machine 4H5H Tolerance Screw Thread Insert (STI) Taper Tap.

PowerCoil wire thread inserts are installed into oversize tapped holes.

Only PowerCoil STI (Screw Thread Insert) Taps are suitable for use with PowerCoil Wire Thread Inserts.

STI Taps have a larger diameter, than standard taps, but the same pitch to accommodate the wire thread insert.

Once the insert is installed in the tapped hole it creates the desired internal thread tolerance for the installed bolt or stud.

Bottoming Taps have a lead of two threads and are used to ensure minimum thread run-out when tapping to the bottom



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

of a blind hole.

Taper Taps have a lead of eight threads and are used as a starting tap in difficult or high precision holes.

Options

3520-5.00T

3520-6.00T

3520-8.00T