



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## STI MC BOTTOMING HSS TAP BY BORDO



SKU	Option	Part #	Price
8720738	Size: 5mm x 0.8mm	3520-5.00B	\$44.72
8719062	Size: 6mm x 1.0mm	3520-6.00B	\$45
8719065	Size: 8mm x 1.25mm	3520-8.00B	\$52

Model	
Type	Bottoming Tap
SKU	8720738
Part Number	3520-5.00B
Barcode	9326518071808
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



Metric Coarse.

HSS Hand and Machine 4H5H Tolerance Screw Thread Insert (STI) Bottoming Tap.

PowerCoil wire thread inserts are installed into oversize tapped holes.

Only PowerCoil STI (Screw Thread Insert) Taps are suitable for use with PowerCoil Wire Thread Inserts.

STI Taps have a larger diameter, than standard taps, but the same pitch to accommodate the wire thread insert.



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Once the insert is installed in the tapped hole it creates the desired internal thread tolerance for the installed bolt or stud.

Bottoming Taps have a lead of two threads and are used to ensure minimum thread run-out when tapping to the bottom of a blind hole.

Bottoming Taps are typically preceded by the use of a Taper or Intermediate Tap.

**Options**

3520-5.00B

3520-6.00B

3520-8.00B