

950W DIE GRINDER GEP950GPLUS (600627000) BY METABO



SKU	Option	Part #	Price
8720862		600627000	\$769

Model	
Type	Die Grinder
SKU	8720862
Part Number	600627000
Barcode	4007430258229
Brand	Metabo
Technical - Main	
Motor Speed - No Load	2500 - 8700 rpm
Dimensions	
Product Weight (Net Weight)	1.7 kg
Features	
Standard Inclusions	Protective rubber cap
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

Features:

- High torque and compact design thanks to robust planetary gear
- Paddle switch with deadmans function: safe to operate due to an ergonomically integrated non-slip switch
- Spindle lock for simple change of tools
- Aluminium die-cast bearing flange for long service life of the machine
- Vario-Constamatic (VC)- Electronics for work with materials requiring customised speeds, which remain almost constant under load
- Thumbwheel for Speed Preselection
- Electronic safety shutdown of the motor for safe working in case the tool stops unexpectedly
- Restart protection: prevents unintentional start-up after power supply interruption
- Electronic overload protection for long service life
- Precise collar for stationary use
- Removable protective rubber cap for comfortable and safe working
- Slim design for ideal handling
- Precision collet for precise concentricity
- Metabo Marathon motor with patented dust protection for long service life
- The specialist: handy grinder with especially high torque; ideal for grinding inner and outer surfaces in combination with flap wheels (see Accessories)

Specifications:

- No-load speed: 2500 - 8700 rpm
- Rated input power: 950 W
- Output power: 510 W
- Revolutions at rated load: 7200 rpm
- Collar diameter: 43 mm / 1 11/16 "



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Collet chuck bore: 6 mm / 0.2362 "

Weight (without power cable): 1.7 kg / 3.7 lbs

Cable length: 4 m / 13 ft

Vibration

Surface grinding (up to \bar{A} 25 mm): 2.5 m/s²

Surface grinding (up to \bar{A} 50 mm): 2.5 m/s²

Uncertainty of measurement K: 1.5 m/s²

Noise emission

Sound pressure level: 87 dB(A)

Sound power level (LwA): 98 dB(A)

Uncertainty of measurement K: 3 dB(A)

Includes:

Collet 6 mm

Protective rubber cap

Side handle

1 Open-jawed spanner