

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

## 800W ROTARY HAMMER DRILL D25133K-XE BY DEWALT



1000

SKU	Option	Part #		Price
8721586		D25133K-XE		\$319
Model				
Туре			Rotary Hammer	
SKU			8721586	
Part Number			D25133K-XE	
Barcode			5035048480618	
Brand			Dewalt	
Packaging + Ship	ping			
Shipping Weight (Gross)			1.48 kg	

## Features:

Ideal for drilling anchor and fixing holes into concrete and masonry from 4 to 26 mm in diameter Rotation-stop for light chiselling applications in brick, soft masonry and occasionally concrete Impact-stop for drilling in wood, steel, ceramic and screwdriving applications Mechanical clutch eliminates sudden high-torque reaction should the bit jam Electronic variable speed for total control in any application Ergonomic rubber coated back handle design for improved comfort in use Rounded ergonomic industrial design allows easy and comfortable handling in any application Improved sealing for maximum protection from dust ingress ensuring long tool life Output air slots designed to protect usersâ€<sup>~</sup> eye Specifications: Tool Holder: SDS-Plus Power Input: 800 Watts Power Output: 640 Watt Impact energy (EPTA 05/2009): 2.6 J No Load Speed: 0-1500 rpm Blows per Minute: 0-5500 bpm Max. Drilling Capacity [Concrete]: 26 mm Max. Drilling Capacity [Core bit]: 50 mm Max. Drilling Capacity [Wood]: 30 mm Max. Drilling Capacity [Metal]: 13 mm Weight: 2.6 kg Length: 335 mm Height: 210 mm Width: 75 mm



2

## 23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

Hand/Arm Vibration - Hammer drilling into concrete: 15.4 m/s

Uncertainty K 1 (Vibration): 1.5 m/s <sup>2</sup> Hand/Arm Vibration - Chiselling: 14.9 m/s <sup>2</sup> Uncertainty K 2 (Vibration): 1.5 m/s <sup>2</sup> Hand/Arm Vibration - Drilling into metal: Uncertainty K 3 (Vibration): 1.5 m/s <sup>2</sup> Hand/Arm Vibration - Screw driving without impact: Uncertainty K 4 (Vibration): 1.5 m/s <sup>2</sup> Sound Pressure: 89 dB(A) Sound Pressure Uncertainty: 3.8 dB(A) Sound Power: 100.1 dB(A) Sound Power Uncertainty: 3.8 dB(A) **Includes:** Multi position rubber side handle Depth stop Heavy duty carrying case