

310ML CARTRIDGE OF FIRECRYL FR FIRE RANGE IN GREY 131479 BY SOUDAL



SKU	Option	Part #	Price
8722289	Style: 310ml Cartridge, Qty: Box of 12	131479	\$10.3
8200555-12	Style: 600ml Sausage, Qty: Box of 12	131478	\$144

Model	
Type	Fire Retardant Sealant
SKU	8722289
Part Number	131479
Barcode	5411183027558
Brand	Soudal
Technical - Main	
Technical Data Sheet (TDS)	https://www.soudal.com.au/pdf/TDS-Soudal-Firecryl-FR.pdf
Safety	
Material Safety Data Sheet (MSDS)	https://www.soudal.com.au/pdf/SDS-Soudal-Firecryl-FR.pdf
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg

Firecryl FR is a fire-resistant, smoke-tight, with heat load intumescent plasto-elastic sealant based on acrylic dispersion.

Features & Benefits

Prevents the passage of fire and smoke

Intumesces when exposed to temperatures higher than 120°C

Can be painted over after curing

Very easy to apply

Permanently elastic after curing

Colourfast and waterproof after curing

Very good adhesion on many porous materials

Application

Fire-resistant and smoke-tight indoor applications.



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

As part of the 'Soudal Fire Range' assortment for penetration seals and joints.

Sealing of fire retardant joints in walls and ceiling.

Fire-restardant filling of cracks in concrete and plasterwork.

Applications where the sealant needs to be overpainted with water based paints and varnishes.

Note

We suggest consultation with a fire engineer or certifier prior to application of all fire rated products.

Technical Data

Firecryl FR Technical Data Sheet

Firecryl FR Safety Data Sheet

Firecryl FR VOC Certificate

Firecryl FR Test Report (Plasterboard)

Firecryl FR Test Report (ACC)

Firecryl FR Declaration of Performance (DoP)

Firecryl FR Acoustic Test