

850W IMPACT DRILL DRIVER SBE850-2 BY METABO



SKU	Option	Part #	Price
8722418		600782530	\$329

Model	
Type	Impact Drill Driver
SKU	8722418
Part Number	600782530
Barcode	4007430313225
Brand	Metabo
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

Includes:

- 1 x Futuro Plus keyless chuck
- 1 x Rubber-coated side handle
- 1 x Drilling depth guide
- 1 x Plastic carry case

Features:

- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Thumbwheel for Speed Preselection
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life
- Rotating carbon brush bridge for maximum performance even in anti-clockwise operation, e.g. for the removal of stubborn screws
- Metabo Marathon-motor with dust protection for long service life
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly
- Forward and reverse rotation
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Cable-protecting ball joint for optimal freedom of motion when working

Specifications:

- Voltage: 220-240 V / 50 - 60 Hz
- Rated input power: 850 W
- Output power: 490 W
- Maximum torque: 36 / 14 Nm // 319 / 124 in-lbs
- Drill-Å~ masonry: 20 mm / 25/32 "
- Drill-Å~ concrete: 18 mm / 23/32 "
- Drill Å~ steel: 13 / 8 mm // 1/2 / 5/16 "
- Drill-Å~ soft wood: 40 / 25 mm // 1 9/16 / 1 "
- No-load speed: 0 - 1100 / 0 - 3100 rpm



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Revolutions at rated load: 640 / 1800 rpm

Maximum impact rate: 58900 bpm

Gears: 2

Chuck capacity: 1.5 - 13 mm // 1/16 - 1/2 "

Collar diameter: 43 mm / 1 11/16 "

Drill spindle with hexagonal recess: 6.35 mm / 1/4 "

Drill spindle thread: 1/2 " - 20 UNF

Chuck clamping type: Quick-action Keyless Chuck

Vibration

Drilling in metal: 4.2 m/s²

Uncertainty of measurement K: 1.5 m/s²

Impact drilling concrete: 17 m/s²

Uncertainty of measurement K: 1.5 m/s²

Noise emission

Sound pressure level: 103 dB(A)

Sound power level (LwA): 114 dB(A)

Uncertainty of measurement K: 3 dB(A)

Weight (without power cable): 2.6 kg / 5.7 lbs

Warranty:

3 Years Warranty Covered By Metabo Australia via
Registration