

## 850W IMPACT DRILL DRIVER SBE850-2 BY METABO



SKU	Option	Part #	Price
8722418		600782530	\$329

Model	
Type	Impact Drill Driver
SKU	8722418
Part Number	600782530
Barcode	4007430313225
Brand	Metabo
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

### Includes:

- 1 x Futuro Plus keyless chuck
- 1 x Rubber-coated side handle
- 1 x Drilling depth guide
- 1 x Plastic carry case

### Features:

Vario (V)-Electronics for working at customised speeds to suit various application materials  
Thumbwheel for Speed Preselection  
Robust die cast aluminium gear housing for optimum heat dissipation and long service life  
Rotating carbon brush bridge for maximum performance even in anti-clockwise operation, e.g. for the removal of stubborn screws  
Metabo Marathon-motor with dust protection for long service life  
Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly  
Forward and reverse rotation  
Spindle with hexagonal recess for screwdriver bits for working without chuck  
Cable-protecting ball joint for optimal freedom of motion when working

### Specifications:

Voltage: 220-240 V / 50 - 60 Hz  
Rated input power: 850 W  
Output power: 490 W  
Maximum torque: 36 / 14 Nm // 319 / 124 in-lbs  
Drill- $\tilde{\sim}$  masonry: 20 mm / 25/32 "  
Drill- $\tilde{\sim}$  concrete: 18 mm / 23/32 "  
Drill  $\tilde{\sim}$  steel: 13 / 8 mm // 1/2 / 5/16 "  
Drill- $\tilde{\sim}$  soft wood: 40 / 25 mm // 1 9/16 / 1 "  
No-load speed: 0 - 1100 / 0 - 3100 rpm



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Revolutions at rated load: 640 / 1800 rpm

Maximum impact rate: 58900 bpm

Gears: 2

Chuck capacity: 1.5 - 13 mm // 1/16 - 1/2 "

Collar diameter: 43 mm / 1 11/16 "

Drill spindle with hexagonal recess: 6.35 mm / 1/4 "

Drill spindle thread: 1/2 " - 20 UNF

Chuck clamping type: Quick-action Keyless Chuck

Vibration

Drilling in metal: 4.2 m/s<sup>2</sup>

Uncertainty of measurement K: 1.5 m/s<sup>2</sup>

Impact drilling concrete: 17 m/s<sup>2</sup>

Uncertainty of measurement K: 1.5 m/s<sup>2</sup>

Noise emission

Sound pressure level: 103 dB(A)

Sound power level (LwA): 114 dB(A)

Uncertainty of measurement K: 3 dB(A)

Weight (without power cable): 2.6 kg / 5.7 lbs

**Warranty:**

3 Years Warranty Covered By Metabo Australia via  
Registration