

1300W IMPACT DRILL DRIVER SBEV1300-2S BY METABO



SKU	Option	Part #	Price
8722802		600786500	\$519

Model	
Type	Impact Drill Driver
SKU	8722802
Part Number	600786500
Barcode	4007430312693
Brand	Metabo
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

1300W Impact Drill Driver SBEV1300-2S by Metabo

Includes:-

- 1 x Futuro Plus keyless chuck
- 1 x Rubber-coated side handle
- 1 x Drilling depth guide
- 1 x Plastic carry case

Features:

Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load

Thumbwheel for Speed Preselection

Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces

Robust die cast aluminium gear housing for optimum heat dissipation and long service life

Rotating carbon brush bridge for maximum performance even in anti-clockwise operation, e.g. for the removal of stubborn screws

Metabo Marathon-motor with dust protection for long service life

Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly

Forward and reverse rotation

Keyless chuck and spindle stop gear for convenient one-handed tool change

Spindle with hexagonal recess for screwdriver bits for working without chuck

Overload protection: protects the motor from overheating

Restart protection: prevents unintentional start-up after power supply interruption

Cable-protecting ball joint for optimal freedom of motion when working

Wear Indication for Carbon Brush



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Specifications:

Rated input power: 1300W

Output power: 730W

Maximum torque:

Speed 1: 44Nm

Speed 2: 16Nm

Max drilling capacity:

Masonry: 24mm

Concrete: 22mm

Steel:

Speed 1: 16mm

Speed 2: 10mm

Soft wood:

Speed 1: 40mm

Speed 2: 25mm

No-load speed:

Speed 1: 0 - 1100rpm

Speed 2: 0 - 3100rpm

Maximum impact rate: 58900bpm

Gears: 2

Chuck capacity: 1.5mm - 13mm

Collar diameter: 43mm

Drill spindle with hexagonal recess: 6.35mm

Drill spindle thread: 1/2 " - 20 UNF

Chuck clamping type: Quick-action Keyless Chuck

Weight (without power cable): 2.8kg

Vibration:

Drilling in metal: 4.2m/s²

Uncertainty of measurement K: 1.5m/s²

Impact drilling concrete: 17m/s²

Uncertainty of measurement K: 1.5m/s²

Noise emission:

Sound pressure level: 103dB(A)

Sound power level (LwA): 114dB(A)

Uncertainty of measurement K: 3dB(A)

Warranty:

3 Years Warranty Covered By Metabo Australia via
Registration