


## 18V 180MM ANGLE GRINDER BARE (TOOL ONLY) WB18LTX BL 180 (613087840) BY METABO



SKU	Option	Part #	Price
8723201		613087840	\$439

Model	
Type	Angle Grinder
SKU	8723201
Part Number	613087840
Barcode	4007430318091
Brand	Metabo
Technical - Main	
Motor Speed - No Load	8200 rpm
Brushless Motor	✓
Dimensions	
Product Weight (Net Weight)	2.6 kg
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

Same cutting depth like a large mains angle grinder with  $\sim 230$  mm; ideal for cutting jobs on the roof

Unique encapsulated Metabo brushless motor with optimum protection from dust provides quick work progress and the highest efficiency

Slim design for prolonged comfort when working overhead or in areas with limited space

Fast brake system for highest user safety stops the disc within a matter of seconds after switching off

Tool-free adjustable guard; twist-proof

Battery pack can be swivelled for better access in hard to reach places

Electronic safety shutdown: reduces kickback if the disc stops unexpectedly - for high user safety

Overload protection, soft start and restart protection

Detachable dust protection filter protects motor from coarse particles

Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

The machine shown may differ in equipment and technical details depending on the configuration. **Specifications:**

Grinding wheel  $\sim 180$  mm / 7 "

No-Load Speed: 8200 rpm

Spindle thread: M 14

Weight (including battery pack): 2.6 kg / 5.7 lbs kg

**Vibration:**

Surface grinding:  $8.3 \text{ m/s}^2$

Uncertainty of measurement K:  $1.5 \text{ m/s}^2$



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Grinding with sandpaper: 2.5 m/s<sup>2</sup>

Uncertainty of measurement K: 1.5 m/s<sup>2</sup>

**Noise Emission:**

Sound pressure level: 82 dB(A)

Sound power level: 93 dB(A)

Uncertainty of measurement K: 3 dB(A)

**Includes:**

Guard

Inner support flange

Nut with two holes

Side handle

Dust protection filter

Flat-pin spanners

MetaLoc case

Without battery pack, without charger