

125MM 1900W RENOVATION GRINDER (RSEV 19-125) 603825710 BY METABO



SKU	Option	Part #	Price
8724107		603825710	\$1359

Model	
Type	Renovation Grinder
SKU	8724107
Part Number	603825710
Barcode	4007430313638
Brand	Metabo
Dimensions	
Product Weight (Net Weight)	3.5 kg
Packaging + Shipping	
Shipping Weight (Gross)	3.5 kg



For effective spot grinding and removal of concrete, screed and coatings with diamond cup wheels
 Maximum productivity thanks to 1,900 Watt strong Metabo Marathon-motor with low weight
 High torque and overload capacity for demanding applications in continuous use
 Low weight, ideal for sanding walls and ceilings
 Perfect ergonomics thanks to slim handle for maximum control and easy working overhead
 Working close to edges thanks to integrated folding segment
 Optimum extraction results: spring-mounted brush rim at the protective cover that adapts to any surface and segment height
 Front handle for safe and uniform guidance when polishing, adjustable without tools
 Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
 Electronic soft start for smooth start-up
 Restart protection: prevents unintentional start-up after power supply interruption
 Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly
 Connection for dust extraction Ø 35/41 mm

Specifications:

Cup wheel Ø: 125 mm / 5 "
 Torque: 5 Nm / 44 in-lbs
 No-load speed: 3800 - 8200 rpm
 Rated input power: 1900 W
 Output power: 1240 W
 Speed at rated load: 6800 rpm
 Spindle thread: M 14
 Weight (without power cable): 3.5 kg / 7.7 lbs
 Cable length: 4 m / 13 ft



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Vibration

Surface grinding: 6.94 m/s²

Uncertainty of measurement K: 1.5 m/s²

Noise emission

Sound pressure level: 92 dB(A)

Sound power level (LwA): 103 dB(A)

Uncertainty of measurement K: 3 dB(A)

Includes:

Bow-type handle

Inner support flange

Nut with two holes

Diamond cup wheel concrete "professional"

Flat-pin spanners

Plastic carry case