

## 23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

## 150MM (6") 350W RANDOM ORBITAL SANDER SXE 150-5.0 BL (615050700) BY METABO





| SKU     | Option | Part #    | Price |
|---------|--------|-----------|-------|
| 8724490 |        | 615050700 | \$989 |
|         |        |           |       |
|         |        |           |       |







Extremely light and flat random orbital sander with symmetrical design for easy change of hands or operation with two hands

Orbit diameter 5 mm for maximum material removal with good surface quality

Non-slip paddle switch with dead man function for safe starting and optionally also control of the speed Vario Tacho Constamatic (VTC) Full-wave Electronics for grinding with materials requiring customised speeds, which remain constant under load

Electronic presetting of the desired speed range Soft start minimises surface damage when placing the machine on the work surface

Unique Metabo brushless motor highest efficiency when grinding, also in continuous mode

Low vibrations for convenient continuous mode

Overload protection: protects the motor from overheating Separate main switch protects from unintentional start Motor and plate brake permits quick placing down of the machine after use

Extraction possibility by means of connecting an all-purpose vacuum cleaner

Multi-hole sanding pad for effective extraction and a longer service life of the sanding medium

When working with 125 mm sanding sheets, the sanding pad "multi-hole"  $\tilde{\rm A}^{\sim}$  125 mm can be used (accessory 630264000) Service-friendly with exchangeable cable



## 23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

The machine shown may differ in equipment and technical details depending on the configuration. **Specifications:** 

Diameter of backing pad: 150 mm / 5.91  $^{\circ}$ 

No-load speed: 4000 - 10000 rpm

Rated input power: 350 W

Revolutions at rated load: 10000 rpm

Orbit diameter: 5 mm / 0.2 "

Weight (without power cable): 1 kg / 2.2 lbs

Cable length: 4.3 m

Vibration:

Surface grinding: 3.4 m/s <sup>2</sup>

Noise emission:

Sound pressure level: 71 dB(A)
Sound power level (LwA): 82 dB(A)
Uncertainty of measurement K: 2 dB(A)

Includes:

Sanding pad "multi-hole" with hook and loop

Open-jawed spanner

MetaLoc case