

## SOUDASEAL FR (FIRE RETARDANT) FIRE RANGE SEALANT 137450 / 131480 / 155483 BY SOUDAL



SKU	Option	Part #	Price
8724693-12	Size: 290ml Cartridge, Colour: Grey, Qty: Box of 12	137450	\$228
8730292-12	Size: 600ml Sausage, Colour: Grey, Qty: Box of 12	131480	\$276
8730291-12	Size: 600ml Sausage, Colour: Limestone, Qty: Box of 12	155483	\$276

Model	
Type	Fire Retardant Sealant
SKU	8724693-12
Part Number	137450
Barcode	5411183157941
Brand	Soudal
Technical - Main	
Colour Name	Grey
Material	100% Acrylic
Country of Origin	
Manufactured in	Belgium
Packaging + Shipping	
Shipping Weight (Gross)	4.0 kg

Soudaseal FR is a high-quality, fire-resistant, smoke-tight, neutral, elastic, one component joint and adhesive sealant based on SMX Polymer (Hybrid).

### Features & Benefits

- High level of Retardation
- Permanently elastic after curing (without fire load)
- Outstanding bond strength on nearly all surfaces, even on slightly wet surfaces
- Very good mechanical characteristics
- Easy to use and apply, also under difficult circumstances.
- Colourfast and UV resistant
- Paintable
- No bubble formation within sealant (in high temperature and humidity applications)
- Does not contain isocyanates, solvents or halogens

### Application

Fire retardant expansion and connection joints in the construction industry.



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Sealing of fire-retardant joints in prefab buildings and  
skyscrapers.

Flexible connections in automotive applications.

As part of the 'Soudal Fire Range' assortment for penetration  
seals and joints.

**Packaging Options**

Item Code	Size	Colour	Unit/box
137450	290 mL cartridge	Grey	12
131480	600 mL sausage	Grey	12
155483	600 mL sausage	Limestone	12

**Note**

We suggest consultation with a fire engineer or certifier prior  
to application of all fire rated products.

**Technical Data**

Technical Data Sheet

Safety Data Sheet

VOC Statement

Test Report (Plasterboard)

Test Report (AAC)

Acoustic Test

Declaration of Performance (DoP)

**Options**

137450

155483

131480