



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## 680G (24OZ) NORMALISED BALL PEIN HAMMER WITH STEEL CORE AND FIBREGLASS HANDLE 7HBPFRH0.675 BY MUMME



| SKU     | Option | Part #       | Price   |
|---------|--------|--------------|---------|
| 8725064 |        | 7HBPFRH0.675 | \$113.5 |



| Model                   |                             |
|-------------------------|-----------------------------|
| Type                    | Normalised Ball Pein Hammer |
| SKU                     | 8725064                     |
| Part Number             | 7HBPFRH0.675                |
| Barcode                 | 9314572012790               |
| Brand                   | Mumme                       |
| Size                    | 680g (24Oz)                 |
| Technical - Main        |                             |
| Material                | Steel Core                  |
| Country of Origin       |                             |
| Manufactured in         | Australia                   |
| Packaging + Shipping    |                             |
| Shipping Weight (Gross) | 1.48 kg                     |

### Features

Useful for engineers and used in metal work for striking punches and chisels

Hammer ball end for riveting work

Hammer heads are pinned through the steel core of the fiberglass handle for added safety

Hammer heads are pinned through the steel core of the fiberglass handle for added safety

Head is forged then normalised for a softer face (below 20HRC) that will mushroom, for applications where risk of chipping needs to be minimised

Head is forged then normalised for a softer face (below 20HRC) that will mushroom, for applications where risk of chipping needs to be minimised

Head is forged then normalised for a softer face (below 20HRC) that will mushroom, for applications where risk of chipping needs to be minimised

Head is forged then normalised for a softer face (below 20HRC) that will mushroom, for applications where risk of chipping needs to be minimised