



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

250ML LIQUID BEESWAX BY GILLY'S



SKU	Option	Part #	Price
8725777	Colour: Clear, Size: 1L	LB1L	\$77
8725776	Colour: Clear, Size: 250ml	LB250ML	\$34
8043265	Colour: Clear, Size: 2L	LB2L	\$110
8043266	Colour: Clear, Size: 4L	LB4L	\$198

Model	
Type	Beeswax
SKU	8725776
Part Number	LB250ML
Barcode	9324554000554
Brand	Gilly's
Country of Origin	
Manufactured in	Australia
Packaging + Shipping	
Shipping Weight (Gross)	0.48 kg

Gilly's easy-to-use Liquid Beeswax nourishes your timber, protecting from dryness and enhancing its natural grain. Rich in pure beeswax and natural oils, it can be used on finished or unfinished surfaces and is even suitable for use on a lathe. Simply apply with a soft cloth or paint brush, allow to dry for half an hour then buff using a lint-free cloth or mitt in a circular motion. Enjoy the pleasant fragrance as you polish, knowing it is food safe.

Use For

Raw timber to nourish and prevent cracking/splitting. Ideal for large, rough surface areas. Suitable for both soft and hard woods.

*Thanks to Mélanie from Live Dream Upcycle (footage)
& aurusaudio.com (soundtrack)*

Surface Preparation Ensure the surface is clean and dry before application.

How to Apply Apply with a soft cloth (or brush for carved/irregular areas).

Allow the timber to absorb the oil for 5 minutes, before buffing back with another clean cloth.

Apply 3 coats, if timber is new or dry, repeating the same procedure. Subsequent coats can be applied straight after buffing. Each timber will vary in porosity and dryness, so the number of coats required will vary. Once timber is saturated, there is no need for



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

any more. Take care not to over-apply; residue can become sticky and attract dirt.

Dry time between coats is 5-10 minutes to allow oil to soak in. Allow up to 30 minutes for a completely dry finish.

Gilly's Liquid Beeswax can be reapplied as frequently as required (if the timber becomes dull or dry). There is no need for any extra work, just follow the simple steps above. We would recommend reapplying a light coat every 4-6 months to keep your timber looking fresh. The more oil that has been applied over time, the less it will require for maintenance.

Warm, soapy water for hands and application cloths.

Dry Time

Maintenance

Clean Up