

1500W SDS-MAX COMBINATION HAMMER KHEV 11-52 BL (600767500) BY METABO



SKU	Option	Part #	Price
8726034		600767500	\$1789

Model	
Type	Rotary Hammer
SKU	8726034
Part Number	600767500
Barcode	4061792002630
Brand	Metabo
Technical - Main	
Motor Power (Input)	2HP / 1500W
Brushless Motor	✓
Dimensions	
Product Weight (Net Weight)	12.4 kg
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

Description:

Maximum drilling progress and high breaking performance thanks to maintenance-free brushless motor and high-performance hammer action

Long service life thanks to brushless technology and robust aluminium die-cast housings of gear and motor

Combination hammer with 2 functions: hammer drilling and chiselling

Metabo VibraTech (MVT) with double dampening: Decoupled handle and impact-absorbing counter-oscillating weight actively reduce vibrations for healthy working also in continuous use.

Ergonomically shaped, slim gripping area with large speed control trigger for comfortable working

Easily accessible locking switch for chiselling in continuous mode

Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load

Optional reduction of speed and impact energy for working in softer materials

Electronic soft start for precise spot-drilling

Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly

Restart protection: prevents unintentional start-up after power supply interruption

Overload protection: protects the motor from overheating

Low-dust chiselling and drilling with external dust extraction

ESA max (accessories)

Specifications:

Max. single blow energy (EPTA): 18.8 J

Maximum impact rate: 2360 bpm



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Rated input power: 1500 W
Drill-Ã~ concrete with hammer drills: 52 mm
No-load speed: 200 / 270 rpm
Revolutions at rated load: 200 / 270 rpm
Bit retainer: SDS-max
Collar diameter: 85 mm
Weight (without power cable): 12.4 kg
Cable length: 6 m / 236 7/32 "

Vibration:

Hammer drilling concrete: 14.1 m/s²
Uncertainty of measurement K: 1.5 m/s²
Chiseling: 9.7 m/s²
Uncertainty of measurement K: 1.5 m/s²

Noise Emission:

Sound pressure level: 98 dB(A)
Sound power level (LwA): 110 dB(A)
Uncertainty of measurement K: 3 dB(A)

Includes:

Rubber-coated side handle
Lubricant for tool shank end
Duster
Plastic carry case