

12V 3/8" DIGITAL TORQUE WRENCH BARE (TOOL ONLY) M12ONEFTR38-0C BY MILWAUKEE



SKU	Option	Part #	Price
8726363		M12ONEFTR38-0C	\$995



Model	
Type	Digital Torque Wrench
SKU	8726363
Part Number	M12ONEFTR38-0C
Barcode	4892210185969
Brand	Milwaukee
Size	3/8"
Technical - Main	
Anvil Size	3/8"
Battery Voltage (V)	12V
Motor Speed - No Load	0 - 100
Brushless Motor	✓
Dimensions	
Product Weight (Net Weight)	2.3 kg
Features	
Standard Inclusions	Bare Tool / Charger (No Battery)
Packaging + Shipping	
Shipping Weight (Gross)	4.1 kg



The M12 FUEL 3/8" Digital Torque Wrench w/ ONE-KEY is the industry's first torque wrench with a motor, delivering increased productivity, precise torque accuracy, and user-demanded reporting functionality. The 3/8" Digital Torque Wrench delivers 50% faster installation time, replacing the hand tool or two-tool installation process and providing more control to reduce the over torquing of fasteners. The 3/8" Digital Torque Wrench provides 13-135 Nm of torque range and accuracy within 2% for torque critical fasteners. This battery powered torque wrench is equipped with ONE-KEY giving the user the power to track, report, and manage your tool. This tool will record all of the fasteners that are saved and produce a downloadable report via ONE-KEY for the necessary parties requiring the data. **Features:** Delivers up to 50% faster installation by replacing the hand tool or two-tool installation process with the POWERSTATE Brushless Motor and torque wrench in the one tool. Faster, more productive torque reporting w/ ONE-KEY providing torque data and customisable reports for inspectors or owners. Adjustable run-down torque to control the tools output torque via the motor to prevent over torque. REDLITHIUM-ION batteries deliver more work per charge and more work over the life of the battery. Four measurement modes (ft-lb, in-lb, Nm, Kgcm).



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Durable design to withstand the most demanding jobsite environments.

Precise torque accuracy of up to $\pm 2\%$ CW, $\pm 3\%$ CCW of full scale for torque critical fasteners.

ONE-KEY technology allows for customisation, tracking, tool security, and inventory management.

REDLINK PLUS Intelligence enables advanced communication between batteries and tools for unmatched performance, protection, and productivity.

Four notification modes that the tool is reaching, meeting or exceeding the torque target (audible, LED, LCD, and vibratory).

Compatible with all M12 batteries & chargers.

Specifications:

ANVIL TYPE: Ball Detent

TORQUE RANGE: 16-203 Nm

RATCHETING ANGLE: 4.5 °

CALIBRATION: 1 Year or 5,000 Cycles

TOOL ACCURACY: CW: $\pm 2\%$ of Full Scale; CCW: $\pm 3\%$ of Full Scale; (Range: 20% - 100% of Full Scale);

DATA STORAGE CAPACITY: 28,500 entries

AVAILABLE PRESETS: 15

Technical Data:

General Power Tool Safety Warning

Operator's Manual (M12ONEFTR38-0C)