

#### 23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

# 20KG BAG OF WALNUT SHELL MEDIA ABRASIVE 16/24 3029T BY TRADEQUIP PROFESSIONAL



SKU	Option	Part #	Price
8726707		3029T	\$190



Model	
Туре	Blasting Media / Garnet
SKU	8726707
Part Number	3029T
Brand	Tradequip
Size	20Kg
Technical - Main	
Colour Name	Walnut
Material	Walnut Shells
Dimensions	
Product Weight (Net Weight)	20 kg
Packaging + Shipping	
Shipping Weight (Gross)	20.0 kg



The TradeQuip "Made for the Trade" Walnut Shell Blasting Media Abrasive is designed for use in conjunction with our *TradeQuip* Blasting Cabinets. Nut shells and other organic materials, don't cause anchor patterns, making them useful for removing dirt, grease, oil, carbon, scale, burrs and paint without changing the underlying substrate. Walnut shells can be an excellent choice for softer surfaces such as wood — they won't cause etching. Walnut shells are one of less abrasive blasting media you can use and are completely biodegradable, making them among the most environmentally-friendly blasting media. Walnut shell blasting media is great for rust-free paint removal from sheet metal and for cleaning engines and transmissions. Walnut media blasting is also an effective media for cleaning paint, grease and other dirt from the surface of a material whilst maintaining the integrity of substrate materials. Ideal for use with aluminium, brass and sheet metal. It has been specified for use with TradeQuip "Made for the Trade" Blasting Cabinets only. Note: TradeQuip Walnut Shells cannot be used in TradeQuip Mobile Blasting Units

### **Features**

Biodegradable environmentally friendly

## A SEYOND

### 23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

Fast removal of dirt, grease, oil and carbon from internal parts

Used for general maintenance and cleaning paint rust free Works well on wood and won't cause etching or anchor patterns

Ideal for preparation of aluminium, brass and sheet metal Widely used for for cleaning engine and transmission parts

### Specifications

Mesh: 16/24 Shape: Sub Angular Hardness: 3.0 - 4.0 MOHS Density: 0.7 - 1.21 SG

Blasting Speed: Up to 10.4 m2/hr

Dust Factor: Low Recyclability: 1/10 Profile Range: 7.25 - 12.2 µ

Profile Range: 7.25 - 12.2

Size: 0.04 - 0.8mm

Consumption Rate: 10.4-34kg/m2

Weight: 20kg

NOTE: TradeQuip Walnut Shells cannot be used in TradeQuip

Mobile Blasting Units.

**NOTE:** We recommend the use of personal protective equipment. Always wear a respiratory filter or mask over your mouth when operating this unit. You will create a cloud of abrasive media material and debris which should not be inhaled.