

12,000KG AIR / HYDRAULIC BOTTLE JACK TQBJ12TA BY TRADEQUIP PROFESSIONAL



SKU	Option	Part #	Price
8727010		TQBJ12TA	\$239

Model	
Type	Bottle Jacks
SKU	8727010
Part Number	TQBJ12TA
Barcode	9332105010495
Brand	Tradequip
Size	12000Kg
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

This **Tradequip "Made for the Trade"** Air/ Hydraulic Bottle Jack is designed to operate pneumatically. The power of air makes it easy to lift farm vehicles, trucks, lawn mowers, heavy duty machinery, industrial construction equipment and more. With it's low profile design this 12,000kg heavy-duty air/hydraulic bottle jack is the perfect choice for a wide variety of uses. Use this workhorse with a 110-125 PSI rated air pressure supply to lighten the load and provide the fast, strong lifting power you need. The 260"510mm lift range raises the load to the desired height and a knurled, heat-treated pad with screw height adjustment allows fine-tune of the jack from there.

Carelessness can cause injuries, but this jack gives you extra peace of mind. It's fitted with a safety overload valve for extra protection. Even if you load the jack up with too much weight, the safety overload kicks in and gently lowers the unit before the operator is put in a dangerous situation. Designed for professional durability, the rugged high-grade steel frame is teamed with a lead-free paint finish that covers the entire surface to ensure long-lasting wear and help prevent rust. The paint is oil, grease and dirt resistant for easy cleanup no matter how often you put this jack to work.

Features:

- Machined and polished cylinders with die-cut threads
- Fabricated from hard-cast steel with heat-treated critical stress areas
- Unique cross-type forged release valve assures positive load control
- Built-in bypass protection prevents damage from over pumping
- Compact yet powerful Air Turbo motor



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Versatile quick connector provides quick & easy air connection

Two piece pump handle

Convenient welded carry handle

Specifications:

Safe Working Capacity: 12,000kg

Minimum Height: 260mm

Maximum Height: 510mm

Hydraulic Stroke: 170mm

Screw Extension Height: 80mm

Operating Air Pressure: 110-125psi

Air Fitting: 1/4"

Carton: 250x180x270mm

Gross Weight: 12.75kg

IMPORTANT: NEVER get beneath a vehicle that is only supported by a jack. ALWAYS chock the vehicle wheels and use support stands. Intended Use:

For heavy duty use on truck, agriculture, construction, mining, automotive, and marine applications where lifting and lowering is required.