

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

12V FUEL WET DRY VACUUM L CLASS BARE (TOOL ONLY) M12FWDVL-0 BY MILWAUKEE





SKU	Option	Part #	Price
8728050		M12FWDVL-0	\$222

Model		
Туре	Wet / Dry Vacuum	
SKU	8728050	
Part Number	M12FWDVL-0	
Barcode	4892210190864	
Brand	Milwaukee	
Technical - Main		
Battery Voltage (V)	12V	
Runtime	26 minutes	
Brushless Motor	✓	
Dimensions		
Product Length	348 mm	
Product Width	221 mm	
Product Height	302 mm	
Product Weight (Net Weight)	4.5 kg	
Packaging + Shipping		
Shipping Weight (Gross)	1.48 kg	







The M12 FUEL™ Wet/Dry Vacuum L Class is the first cordless 12V wet/dry vacuum of its kind. It delivers users 105 mbar max sealed suction within a compact footprint. With guiet operation of 88 dB(A), it is suitable of use in occupied spaces. The POWERSTATE™ Brushless Motor delivers up to 1,275 I/min airflow (45 CFM) and 105 mbar (1,067 mmHâ,,O) of suction. The stackable design and compact footprint stores neatly in a van or cart, and organised on-board storage conveniently keeps the vacuum attachments inside of the unit. M12 FUEL™ Wet/Dry Vacuum L Class also comes with a wall mount hanging plate, giving users increased storage options. With 14 minutes of runtime on high and 26 minutes on low, the vacuum is ideal for spot and service-focused wet/dry quick clean up needs. The Wet/Dry Vacuum comes with a flexible hose, crevice tool, utility nozzle, wall mount, DEK26 Connector and HEPA filter. Features:

POWERSTATE™ Brushless Motor 1,275 I/min air flow (45 CFM)

105 mbar (1,067 mmHâ,,O) water lift provides suction for wet and dry applications

Sound power level of 88 dB(A)

On-board accessory storage

6.1 L capacity

Built-in blower port

High/low switch

Stackable design for storage and transportation

PEYOND

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

Wall mount for storage versatility

Specifications:

Max Air Flow: 1,275 l/min (45 CFM)

Sealed Suction in Water: 105 mbar (1,067 mmHâ,,O)

Diameter: 31.8 mm (1-1/4") (Inlet Diameter)

Wet Capacity: 6.1 L Dry Capacity: 5.7 L

Includes:

(1) M12 FUEL $^{\text{\tiny M}}$ Wet/Dry Vacuum L Class (M12FWDVL-0)

(1) Utility Tool

(1) Crevice Tool

(1) 1.5 m Flexible Hose

(1) Wall Mount

(1) DEK26 Connector

(1) HEPA Filter

(Not Included) Battery & Charger

Resources:

General Power Tool Safety Warning Operator's Manual (M12FWDVL-0)