

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

MIG + STICK + TIG WELDER WF-255MST 250AMP WF-06167 BY WELDCLASS





SKU	Option	Part #	Price
8728245		WF-255MST	\$2149

Model	
Туре	MIG / Stick / TIG Welder
SKU	8728245
Part Number	WF-255MST
Barcode	9341562061674
Brand	Weldclass
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg



The Weldforce 255MST delivers an impressive 250A @ 35% output, plus a host of impressive features to make your job easier. Work in manual mode, or synergic (select the material and thickness, and the machine takes care of the settings). PFC technology means the WF-205MST is extremely power efficient, delivering higher duty cycle and allowing use on long extension leads (up to 100m) and a great machine for use with generators where required. Stick/MMA & lift-TIG capability, job memory, 4-roll geared drive system, fan-ondemand to reduce dust intake, spool gun ready, advanced Stick and TIG functions... and a stack of other features too numerous list here! Comes with 4m MIG torch, 2-stage gassaving regulator, full set of drive rollers for gas, gasless & aluminium wire, 4m earth and stick leads, 15A plug fitted, and cable strap system. Maximum recommended MIG welding capacity of 12mm (mild steel).

FUNCTIONS

MIG (Gas / Gasless) Stick / MMA TIG (Lift-Arc)

AT A GLANCE:

250A max MIG output @ 35% duty cycle Weld up to 12mm Mild Steel (max MIG capacity) Fitted with 15A 240V plug

KEY FEATURES:

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

Power Factor Correction (PFC) - reduced power draw, increased duty-cycle, ideal for long leads & generators Manual or Synergic (enter material type & thickness and machine will set parameters automatically) 20+ Pre-set Programs - for different materials Job Save - store custom settings for up to 20 jobs Geared 4-Roll Wire Drive System - for super reliable wirefeeding

Takes 5kg (D200mm) or 15kg (D300mm)spools

Spool Gun Ready

Generator Compatible - min 13kva, ideal 15+kva

Fan-on-Demand - reduces dust intake

Stressed-Tested - to 440V & over-specified componentry for reliability

3 year warranty*

5 year warranty

Robust & Portable, weighs 26kg

Optional Stick/MMA VRD function (Supplied as standard with

VRD NOT active. VRD can be activated by an authorised

agent/distributor if required)

MIG functions & adjustments include: Inductance, Soft Start, Burnback, Post-Gas Time, 2T/4T Trigger, Spot/Stitch Time Stick/MMA functions & adjustments include: Hot-Start %, Arc-Force

TIG functions & adjustments include: Trigger & Remote Amperage Control on the the torch, Post-Gas Time, Slope-

Down Time

INCLUDES:

MIG Torch 4m BZL 25

Earth Lead H/Duty 4m

Stick Lead H/Duty 4m

Gas Regulator

Driver Roller for 0.6/0.8mm steel/solid wire

Driver Roller for 0.9/1.2mm steel/solid wire

Driver Roller for 0.8/0.9mm gasless wire

Driver Roller for 1.0/1.2mm aluminium wire

Cable Retaining Strap

Long Power Input Lead 3m

OPTIONAL ACCESSORIES:

Spool Gun BZL 25 8m (part no WC-06203)

TIG Torch #17 4m with Remote Control (part no WC-06234)

T100 Welding Trolley (part no WC-06235)

COMMON SPARE PARTS:

MIG Torch Spares (BZL 25)

Drive Rollers

RELATED INFO & ARTICLES:

Warranty Registration

What is an Inverter Welder (or plasma cutter)? About Inverter technology

What is Duty Cycle & How is it Calculated?

Using Generators to power inverter welders & plasma cutters

What is MMA (stick) welding? About the MMA process

MMA (Stick) Welding: What is Hot Start, Arc Force & Anti-Stick?

MMA (Stick) Welding: What is Open Circuit Voltage (OCV)?

What is TIG welding? About the TIG process

TIG Welding: What is Scratch-Start, Lift-Arc and HF Ignition?

*Standard warranty 2 years, with 1 year extension if

registered at Weldclass.com.au/WeldforceWarranty **15 Amp

plug fitted for commissioning purposes only. To obtain full



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

output, 25A or 32A plug & 4.0mm input cable should be installed by the user.

DOWLOADS:

Download Instruction Manual Download User Guide Download Fact Sheet