



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## 3/8" 120XP FLEX HEAD ELECTRONIC TORQUE WRENCH WITH ANGLE 85195 BY GEARWRENCH



SKU	Option	Part #	Price
8728833		85195	\$567.95



Model	
Type	Digital Wrench
SKU	8728833
Part Number	85195
Barcode	099575851957
Brand	GearWrench
Size	3/8"
Technical - Main	
Material	Full Polish Chrome
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg



### Features:

120XP™ head provides a 3 ° ratcheting arc to turn fasteners in narrow spaces

Low profile tube, 15 ° flex teardrop head, and flush mounted on/off switch allow for better access in tight confines

Digitally tracks torque and angle measurements. Vibrating handle, buzzer, and LCD screen alert when target torque is reached

3 function modes feature peak torque, angle, and peak angle for additional versatility

5 torque measurement units provide a readout in ft-lb, in-lb, Nm, Kg-m, and Kg-cm

10 available preset torque settings allow you to quickly access frequently repeated applications

Torque accuracy of +/-2% CW and +/-3% CCW between 20% and 100% of wrench capability Angle settings offer +/-1% of reading of angle accuracy

Knurled aluminum handle lets you grip comfortably, while clearly marked midpoint promotes additional accuracy

Meets or exceeds ASME standards and specifications

1 year limited warranty; calibration accuracy warranted for 90 days

### Specifications:

Overall Length 16.02 in

ASME Specification B107.10 B107.12 B107.28 B107.300

Drive Type Square



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Drive Tang Size 3/8 in

Knurled Yes

Tooth Count 120XP™

Head Thickness .72 in

Head Width 1.25 in

Finish Full Polish Chrome

Min Torque (Primary Scale) 10 ft/lb

Max Torque (Primary Scale) 100 ft/lb

Alt Scale Increments .1 Nm

Primary Scale Increments .1 ft/lb

Min Torque (Alt Scale) 13.5 Nm

Max Torque (Alt Scale) 135 Nm

Head Thickness Less Tang .72 in

Torque Accuracy (20-100% of Full Range) +/-2% Clockwise

Head Length 2.12 in

Material Alloy Steel

**Includes:**

Calibration certificate

Blow mould case