



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

200MM UNIVERSAL DETECTOR AND WALL SCANNER D-TECT200 (06010816K0) BY BOSCH



SKU	Option	Part #	Price
8728982		D-TECT 200	\$1489

Model	
Type	Wall Detector / Scanner
SKU	8728982
Part Number	D-TECT 200
Barcode	3165140988124
Brand	Bosch
Size	200mm
Dimensions	
Product Weight (Net Weight)	0.64 kg
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

Scan and spot the unseen. The D-tect 200 C Professional offers a maximum detection depth of up to 200mm, featuring innovative object depth indication. Thanks to the 3.5" color screen and intuitive button layout, the D-tect 200 C Professional can be easily operated and clearly visualize most common objects behind multiple wall types. The ability to take screenshots supports instant documentation where images can be easily transferred via USB-C and micro-SD card slot and the tool is dual-power source compatible with select batteries from the Bosch 12V platform or 4 x AA Alkaline for longer run time. Together with 3 various detection types including object detection, advanced water leakage detection, and distance measuring functions the D-tect 200 C Professional is an all-round reliable solution that fulfills applications from all trades.

Bosch Radar Technology to achieve 200mm maximum detection depth and identification of most common objects

Dual power source for longer run time (12V or 4 x AA)

3.5" Colour Display for easy readout

Quick and easy documentation via screenshot function and export via USB-C or SD card

Accuracy: ± 0.5 cm to ± 1 cm

IP 5X

Detectable materials: Metal (ferrous and non-ferrous), Cable (live and non-live wire), Wood and plastic pipes

Detectable wall types: Brick/ Universal, concrete, early age concrete, drywall, panel heating, vertical coring brick and horizontal coring brick

Specifications:

Detectable objects: magnetic metals (e.g. iron), non-magnetic metals (e.g. copper), live cables, low-voltage & data cables (Three-phase power cables, cavities), non-live



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

cables, wooden substructures, water-filled plastic pipes,

Empty plastic pipes

Additional function: Leakage detection, distance measurement

Detection depth, other wall types, max.: 80 mm

Power supply: 12 V Li-Ion battery, 10.8 V-LI ION battery, 4 x 1.5 V LR6 (AA)

Bosch Radar Technology: yes

Dust and splash protection: IP 5X

Wall types: Concrete, Early age concrete, Drywall, Brick/Universal, Horizontal coring brick, Vertical coring brick, Panel Heating

Detection depth, non-magnetic metal, max.: 80 mm

Detection depth, magnetic metal, max.: 200 mm

Accuracy: ± 5 mm

Detection depth, dry concrete, max.: 200 mm

Detection depth, early age concrete, max.: 60 mm

Views Object: view, Spot view, Signal View, Signal View 2D

Updatable: yes

Documentation: via USB-C, SD-Card

Material identification: Magnetic metal, Non-magnetic metal,

Non-metal material, Live cable

Max. detection depth: 200 mm

Detection depth, live cables, max.: 200 mm

Detection depth, wooden substructures, max.: 38 mm