



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## KITCHEN BENCH OIL (CLEAR) BY GILLY'S



SKU	Option	Part #	Price
8729237	Size: 1L	KBO1L	\$77
8729236	Size: 250ml	KBO250ML	\$34
8043278	Size: 4L	KBO4L	\$198

Model	
Type	Kitchen Bench Oil
SKU	8729236
Part Number	KBO250ML
Barcode	9324554000967
Brand	Gilly's
Country of Origin	
Manufactured in	Australia
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg

A tung oil based finish designed for timber bench tops, tables and other surfaces in need of a hard wearing natural finish. Kitchen Bench Oil contains natural oils such as tung oil which helps to seal timber and protect it from general wear.

Importantly, it will also repel water. This makes it a great product for kitchen benches, laundry benches and bathroom benches that feature timber tops that may get exposed to water.

This oil contains no lacquer or silicon unlike many products on the market, which means easier maintenance for you and a beautiful natural finish. It will highlight the nuances of your selected timber and prolong its natural look.

### Use For

Kitchen benches, bathroom & laundry benches, cabinetry, butcher blocks, dining tables, window frames

Ensure the surface is clean and dry before application. D-limonene (natural citrus solvent) or a turpentine can be used for a vigorous clean. For a lighter clean, you can use an all purpose cleaner.

### Surface Preparation

If there is any oil, wax, grease, dirt or similar residue on the surface, it may affect the tung oil's ability to cure - so a thorough clean is important.

### How to Apply

Rub or brush oil into the timber. Lighter coats are better.

On first coat, let it sit for 5 minutes after applying. Wipe on more oil to areas that



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

become dull, as the oil soaks in.

After 5 more minutes, wipe off any excess oil with another clean cloth and rub it back vigorously.

Follow this procedure for each

coat. *Note: Some people prefer to wet sand between coats, however this is generally only for timber that is quite porous.*

Apply 3 coats. Best to wait 24 hours between coats (curing time can be up to 30 days).

Apply more coats if desired or necessary.

Hang out any rags or soak in water, rather than leaving scrunched up, as there is the potential for combustion.

24 hours to dry between coats. As this is tung oil based, it can take 4 weeks to completely cure. Light usage is however perfectly fine within this time.

#### **Dry Time**

This product is built from natural oils, in particular tung oil. This makes for a beautiful natural finish. If you do find the finish gets scratched or damaged, you can simply reapply following the same steps outlined above. There is no need to sand it back as you would have to do with lacquers, varnishes and silicon based products.

#### **Maintenance**

For general maintenance and wear, you can assess as you see fit. We would recommend reapplying a light 1-2 coats every 6-12 months to keep your timber looking fresh!

#### **Clean Up**

D-Limonene or mineral turpentine.