

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

150MM (6") 400W RANDOM ORBITAL SANDER GEX 40-150 (060137B240) BY BOSCH





The high-performance 150mm random orbit sander for professional finishes.

Features:

Housing with a decoupled sanding unit for consistent contact pressure, enabling high-quality surface results Unique vibration damping produces very low vibrations for continuous work

Multi-hole sanding pad for sanding sheets with different hole pattern and for significantly increased dust extraction The GEX 40-150 Professional is Bosch's corded random orbit sander designed for high performance with professional finishes in the 150-mm category. It features a housing with a decoupled sanding unit for consistent contact pressure, providing the highest- quality surface results. Its unique vibration damping produces very low vibrations, allowing for continuous work. The GEX 40-150 is equipped with a multihole sanding pad for sanding sheets with different hole pattern and for significantly increased dust extraction. Equipment & Application

This random orbit sander is intended for sanding, in-between sanding, lacquer removal, finishing surfaces, and polishing. It is applicable on wood, veneer, lacquer, and filler, as well as mineral and acrylic. It is compatible with the Bosch Click & Clean System. Additional Information

SKU	Option	Part #		Price
8729502		060137B240		\$359
Model				
Туре			Sander	
SKU			8729502	
Part Number			060137B240	
Barcode			4059952562933	
Brand			Bosch	
Size			150mm (6")	
Dimensions				
Product Length			409 mm	
Product Width			148 mm	
Product Height			197 mm	
Product Weight (Net Weight)			2.4 kg	
Packaging + Shipping				
Shipping Weight (Gross)			1.48 kg	



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 <u>hello@beyondtools.com</u>

The GEX 40-150 also includes a dust box with a built-in Bosch Micro Filter System, a 150 mm sanding pad fitted with a hook-and-loop system for fastening sanding sheets, speed selection and Vibration Control.

The most important data

Sanding pad diameter	150			
No-load speed	5,500 – 12,000 rpm			
Orbital stroke rate	11,000 – 24,000 opm			
Eccentricity	2			
Sanding sheet / disc attachment Hook-and-loop fastening				
Rated input power	400			
Weight	2.4			
Tool dimensions (width)	148			
Tool dimensions (length)	409			
Tool dimensions (height)	197			
Orbit diameter	4			
Technical Data:				
View Product Data Sheet here.				
View User Manual here.				

WWW.BEYONDTOOLS.COM - © COPYRIGHT 2024 BEYOND TOOLS - VERSION: 20240503