

18V 5.5AH 2PCE BRUSHLESS HAMMER DRILL + IMPACT DRIVER COMBO KIT MET18BL2MB2HD5.5AF AU68200955 BY METABO



SKU	Option	Part #	Price
8729871		AU68200955	\$739

Model	
Type	Combo Kit
SKU	8729871
Part Number	AU68200955
Barcode	9339742000827
Brand	Metabo
Technical - Main	
Amp Hour	4.0Ah
Brushless Motor	✓
Dimensions	
Product Weight (Net Weight)	2.2 kg
Country of Origin	
Manufactured in	Germany
Packaging + Shipping	
Shipping Weight (Gross)	2.48 kg

Includes:

- 1 x Metabo SSD 18 LTX 200 BL - 18V 200Nm Brushless Cordless Impact Driver Skin 602396890
- 1 x Metabo SB 18 LTX BL I - 18V 130Nm Brushless Cordless Hammer Drill Skin 602360850
- 2 x Metabo 5.5 LiHD - 18V 5.5Ah LiHD Battery Pack 625368000
- 1 x Metabo ASC 55 - 12-36 V Air Cooled Charger 627047000
- 1 x Carry Case

Metabo SB 18 LTX BL I - 18V 130Nm Brushless Cordless Hammer Drill Skin 602360850

Features:

- Brushless hammer drill with maximum power for demanding applications
- Hammer drill function for drilling in masonry
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety
- Integrated LED work light with night light function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-system.com

Specifications:

Characteristics

Battery voltage: 18 V

Maximum Torque - soft: 65 Nm / 575 in-lbs

Pulse Torque: 65 Nm / 575 ft. lbs

Maximum Torque, hard: 130 Nm / 1151 in-lbs

Adjustable Torque: 1 - 20 Nm // 9 - 177 in-lbs

Drill-Ø Masonry: 16 mm / 5/8 "

Drill Ø Steel: 13 mm / 1/2 "

Drill-Ø Soft Wood: 68 mm / 2.68 "

No-load Speed: 0 - 550 / 0 - 2000 rpm

Maximum Impact Rate: 38000 bpm

Chuck Capacity: 1.5 - 13 mm // 1/16 - 1/2 "

Weight (including battery pack): 2.2 kg / 4.9 lbs

Vibration

Drilling in metal: 2.6 m/s²

Uncertainty of measurement K: 1.5 m/s²

Impact drilling concrete: 16.5 m/s²

Uncertainty of measurement K: 1.7 m/s²

Noise emission

Sound pressure level: 92 dB(A)

Sound power level (LwA): 103 dB(A)

Uncertainty of measurement K: 3 dB(A)

Metabo SSD 18 LTX 200 BL - 18V 200Nm Brushless

Cordless Impact Driver Skin 602396890

Features:

Compact cordless impact driver with 1/4" hexagon socket and 200 Nm

Unique Metabo brushless motor for quick work progress and highest efficiency for any application

Automatic Power Shift (APS) supports working with self-tapping screws: automatic torque reduction after drilling to prevent overtightening.

Twelve speed/torque levels for a wide range of applications

Integrated work light for illumination of the work area

Robust die cast aluminium gear housing for optimum heat dissipation and durability

Handy belt hook, can be fixed either on the right or left side

Battery packs with capacity display for checking the charge status

Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

Specifications:

Battery voltage: 18 V

Max. no-load speed: 2900 rpm

Maximum impact rate: 4000 bpm

Maximum torque: 200 Nm / 1770 in-lbs

Speed/torque levels: 12

Bit retainer: Hexagon recess 1/4" (6.35 mm)

Weight (including battery pack): 1.3 kg / 2.9 lbs

Vibration

Impact screwdriving: 19.3 m/s²

Uncertainty of measurement K: 2.9 m/s²

Noise emission

Sound pressure level: 94 dB(A)

Sound power level (LwA): 105 dB(A)

Uncertainty of measurement K: 3 dB(A)



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Metabo 5.5 LiHD - 18V 5.5Ah LiHD Battery Pack

625368000

Features:

LiHD battery packs for ultimate performance and extremely long application with minimal temperature generation
Ultra M technology: Intelligent battery management for long-lasting battery packs with a 3 year guarantee
Patented "AIR COOLED" charging technology
Permanent Electronic Single Cell Protection (ESCP) when charging, for particularly long life.
Processor-controlled charge and discharge management
Capacity display with almost no self-discharge
Capacity display with almost no self-discharge
One battery pack for everything. 100% compatibility with all 18 V machines and chargers of the CAS partners:
www.cordless-alliance-system.com

Specifications:

Battery pack voltage: 18 V
Battery pack capacity: 5.5 Ah

Metabo ASC 55 - 12-36 V Air Cooled Charger

627047000

Features:

Monitored charging with microcontroller
Battery diagnosis
Charge time approximately 30 minutes at 1.5 Ah
"AIR COOLED" function
For charging all Li-Power Compact, Li-Power Plus, Li-Power Extreme battery packs
For charging all Li-Ion and LiHD slide-on battery packs (12 V - 36 V) with adapted battery pack charging current
Charger switches to compensation charge: to conserve the capacity, the battery pack is charged for 1 second every 45 seconds with 2.5 ampere.
"AIR COOLED" function: the patented principle is based on air-cooling the battery pack during the charging process. The battery packs are gently cooled down to the required charging temperature, and then during the charging process are constantly maintained at optimum temperature. With this principle, a higher tool life of the battery packs and up to 30% shorter total charging time can be achieved.
"AIR COOLED" function: the patented principle is based on air-cooling the battery pack during the charging process. The battery packs are gently cooled down to the required charging temperature, and then during the charging process are constantly maintained at optimum temperature. With this principle, a higher tool life of the battery packs and up to 30% shorter total charging time can be achieved.

Specifications:

Battery voltage: 12 - 36 V
Mains voltage: 220 - 240 V
Mains frequency: 50 - 60 Hz