



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

125MM 1900W ANGLE GRINDER WEPBA19-125QDS M-BRUSH (613114190) BY METABO



SKU	Option	Part #	Price
8730451		613114190	\$489

Model	
Type	Angle Grinder
SKU	8730451
Part Number	613114190
Barcode	4061792224810
Brand	Metabo
Size	125mm (5")
Packaging + Shipping	
Shipping Weight (Gross)	2.7 kg

Features:

With powerful 1,900 Watt and M-brush technology equipped for industrial use

Metabo M-brush technology: service-free carbon brushes with triple service life for an entire machine life

Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque

Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load

Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System

Tool-free adjustable guard; twist-proof

Low-vibration side handle Metabo VibraTech (MVT)

Best anti-vibration system: integrated auto-balancer for up to 50% less hand-arm vibrations, longer service life of the machine and up to twice the service life of the grinding wheels

Paddle switch with dead man function: safe to operate due to an ergonomically integrated non-slip switch

Fastest brake system for highest user safety: patented, mechanical disc brake stops the disc within 2 seconds after switching off, even in the event of a power cut

Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
Electronic overload protection, soft start and restart protection

Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting

Steel ring to accommodate the carabiner secures the angle grinder against falling when working at great heights

Includes:

Guard

Metabo VibraTech (MVT) side handle

Dust protection filter

Inner support flange

M-Quick flange nut



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Specifications:

Disc-Ø: 125 mm // 5 "

Rated input power: 1900 W

Output power: 1220 W

No-load speed: 11000 rpm

Revolutions at rated load: 11000 rpm

Torque: 4 Nm / 35 in-lbs

Spindle thread: M 14

Handle circumference: 197 mm / 7 3/4 "

Weight (without power cable): 2.7 kg / 6 lbs

Cable length: 4 m / 13 ft

Vibration:

Surface grinding: 4 m/s²

Uncertainty of measurement K: 1.5 m/s²

Grinding with sandpaper: 3 m/s²

Uncertainty of measurement K: 1.5 m/s²

Noise Emission:

Sound pressure level: 93 dB(A)

Sound power level (LwA): 104 dB(A)

Uncertainty of measurement K: 3 dB(A)