



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

# 165MM (6-1/2") X 20MM X 4T FIBRE CEMENT TRACK SAW BLADE PDC 48400670 BY MILWAUKEE



SKU	Option	Part #	Price
8730758		48400670	\$85

Model	
Type	Circular Saw Blade
SKU	8730758
Part Number	48400670
Barcode	045242607662
Brand	Milwaukee
Size	165mm (6-1/2")
Technical - Main	
Teeth	24T
Technical - Saw	
Blade (Main) - Bore Size (mm)	20mm
Blade (Main) - Diameter (Max.)	165 mm
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg



Milwaukee®'s Track Saw Blades are designed to deliver accuracy and finish quality cuts in all Track Saw applications. The 4T Fibre Cement specialty blade has Polycrystalline Diamond (PCD) teeth for up to 75X longer life vs standard blades when cutting fibre cement materials. The low tooth count and large gullet design also help to produce less dust for a healthier jobsite environment. Its laser cut, resin filled vibration slots absorb vibrations and reduce wobble for increased accuracy. An anti-friction PTFE coating protects the blade against heat and friction for cooler, smoother cutting.

### Features:

Designed for use with M18 FUEL™ Track Saw (M18FPS55-0).  
Compatible with all 165x20mm Track/Plunge Saws.  
4T PCD for extended cutting life in all fibre cement materials.  
Low tooth count and large gullet design to produce less dust.  
Laser cut vibration slots: Resin filled slots to absorb vibrations and reduce wobble for increased cutting accuracy.  
Anti-friction coating: Anti-friction PTFE coating for cooler & smoother cuts.

### Specifications:

Fibre cement cladding boards/sheets, trim, moulding