



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

MC CHROME TAP SET 3PCE BY BORDO



SKU	Option	Part #	Price
8730873	Size: 4mm x 0.7mm	4220-4.00TS	\$34
8728430	Size: 5mm x 0.8mm	4220-5.00TS	\$20.5
9804130	Size: 6mm x 1.0mm	4220-6.00TS	\$20.5

Model	
Type	Tap Set
SKU	8730873
Part Number	4220-4.00TS
Barcode	9326518041429
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg

Chrome Alloy Metric Coarse Hand Tap Set.

Used as thread chasers to clean an existing thread.

They can also be used to create a new female thread in non-ferrous metals and plastics.

Chrome alloy taps are not suitable for creating precision, safety or critical threads.

Metric Coarse angle of thread is 60 degrees.

The crest is flat and the thread has clearance at the root allowing external thread and internal thread to engage well.

Larger root radius and lower thread height enable easy screw thread processing and increase thread screw strength.

The major diameter of external thread and pitch are specified by a simple numerical value (most commonly measured in



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

millimetres).

Bottoming Taps have a lead of two threads and are used to ensure minimum thread run-out when tapping to the bottom of a blind hole.

Taper Taps have a lead of eight threads and are used as a starting tap in difficult or high precision holes.

Intermediate Taps have a lead of four threads and are used in most general purpose applications to cut a thread true to a pre-drilled pilot hole.

Bottoming Taps are typically preceded by the use of a Taper or Intermediate Tap.