



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

MF BOTTOMING CHROME TAP BY BORDO



SKU	Option	Part #	Price
8730997	Size: 20mm x 1.5mm	4223-20.00B	\$29.9
8729496	Size: 32mm x 1.5mm	4223-32.00B	\$177

Model	
Type	Bottoming Tap
SKU	8730997
Part Number	4223-20.00B
Barcode	9326518041986
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com



About this item:

Chrome Alloy Conduit (Metric Fine) Bottoming Hand Tap.



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Used as thread chasers to clean an existing thread.

They can also be used to create a new female thread in non-ferrous metals and plastics.

Chrome alloy taps are not suitable for creating precision, safety or critical threads.

Metric Fine angle of thread is 60 degrees.

The crest is flat and the thread has clearance at the root allowing external thread and internal thread to engage well.

Larger root radius and lower thread height enable easy screw thread processing and increase thread screw strength.

The major diameter of external thread and pitch are specified by a simple numerical value (most commonly measured in millimetres).

Bottoming Taps have a lead of two threads and are used to ensure minimum thread run-out when tapping to the bottom of a blind hole.

Bottoming Taps are typically preceded by the use of a Taper or Intermediate Tap.

Options

4223-20.00B

4223-32.00B