

18V 600M RED BEAM DUAL GRADE ROTARY LASER KIT GRL600CHV (0601061F40) BY BOSCH



SKU	Option	Part #	Price
8731073		0601061F40	\$2999

Model	
Type	Rotary Laser Level
SKU	8731073
Part Number	0601061F40
Barcode	4059952519357
Brand	Bosch
Technical - Main	
Laser Colour	Red
Dimensions	
Product Length	327 mm
Product Width	188 mm
Product Height	278 mm
Product Weight (Net Weight)	1.8 kg
Warranty	
Warranty	6 Years
Packaging + Shipping	
Shipping Weight (Gross)	9.6 kg

Heavy duty, jobsite-proof - the robust GRL 600 CHV Professional endures even the harshest environments. Its sturdy design offers impact protection and has an IP68 rating against dust and water - including the battery compartment for highly flexible work in bad weather conditions. It provides convenient connectivity, enabling more focused work with less wasted time. Operating the tool is intuitive thanks to its screen and access to the levelling remote app that visualizes all functions, including a dual slope setting, to save valuable time. This highly accurate laser has a long runtime, both with the 18V battery system and alkaline batteries included for continuous working.

Equipment & Application

Use this tool for exterior applications when determining cut-and-fill excavation work, concrete forms, landscaping, and façade work.

Additional Information

The GRL 600 CHV also features a high-quality receiver with a 125-mm reception area, a dual-sided display, and an offset feature in millimeters. Calibrating the tool is quick and easy - follow the step-by-step instructions via the intuitive app to save time and resources and ensure accurate results on every job. Use the handy 'mask mode' available in the app to avoid reflection and interference with other devices on the jobsite.

Dual-slope setting with digital dial-in of grade (X and/or Y)

IP68 rating plus 2m drop rating

Bluetooth connectivity with additional features in the

Levelling Remote App

Simple and precise user calibration via the app



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Intuitive and easy-to-understand screen and functions on tool

Long battery life - Up to 60 hours with ProCore 18V 4.0Ah

Battery

Specification:

Leveling Accuracy: ± 0.05 mm/m

Working Range (Diameter) W/ Lr 60 Receiver: 600m

IP Rating: IP 68

Self-Leveling Range: $\pm 5^\circ$

Single/Dual Axis Slope Operation: 8.50%

Rotational Speed: 150/300/600 min⁻¹

Scan Angle For Line Operation: 0°/10°/25°/50°

Tripod Mount: 5/8 In.-11

Laser Class: 2

Approx. Operating Time With Li (4.0Ah Procore18V) Battery:

60h

Approx. Operating Time With Alkaline Batteries: 70h

Weight W/ Li (4.0Ah Procore18V) Battery: 4.2 kg

Weight W/ Alkaline Batteries: 4.8 kg

Receiver (LR 60) Reception Area: 125mm

User calibration: Yes, with app

Includes:

GRL 600 CHV Rotary Laser

LR 60 Laser Receiver with RB 60 receiver bracket

RC 6 Remote Control

WM 6 Wall Mount

GAL 18V-40 Li Battery Charger

BA 1 Battery Adapter

4x (D) Batteries

4x AA Batteries

Red Laser Glasses

Red Target Plate

Tripod Carrying Straps

Carrying Case