

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

18V BRUSHLESS IMPACT WRENCH BARE (TOOL ONLY) WR18DH(H4Z) BY HIKOKI



Introducing the 18V Brushless 12.7mm Impact Wrench WR18DH(H4Z) from HiKOKI, a powerhouse tool designed to tackle your toughest tasks with ease. With its top-class tightening torgue of 345Nm, this impact wrench delivers exceptional performance and efficiency. Equipped with an Auto-Stop function, it prevents over-tightening of bolts, ensuring precision and safety in every job. The Auto-Slow function suppresses drop nuts, further enhancing control and stability. Changing sockets is a breeze, thanks to its userfriendly design that allows for easy attachment and removal. Plus, the IP56 rating guarantees dust and water resistance, making it durable and reliable even in challenging working conditions. The WR18DH(H4Z) is a go-to tool for professionals who demand power, versatility, and reliability.

Features:

Top-class tightening torque of 345Nm



SKU	Option	Part #		Price
87433151		WR18DH(H4Z)		\$349
Model				
Туре			Impact Wrench	
SKU			87433151	
Part Number			WR18DH(H4Z)	
Barcode			4966376410446	
Brand			Нікокі	
Size			18V	
Technical - Main				
Battery Voltage (V)			36V	
Drilling Capacity - Bolt			M12 - M30	
Drilling Capacity - H T Bolt			M10 - M24	
Drive Type			19mm (3/4") Square Drive	
Motor Speed - No Load			0 - 1,500 (min-1) (High Mode)	
Features				

Standard Inclusions	Bare Tool Only (No Battery / Charger)
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

23 Exhibition Drive, Malaga Western Australia



Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 <u>hello@beyondtools.com</u>

Auto-Stop function to prevent overtightening of bolts Auto-Slow function to suppress drop nuts Easy to attach and remove the socket IP56 (dust and water resistant) Warranty: Includes 3 Years Standard Warranty and 6 Years Warranty if product is registered online. Specifications Voltage: 18V Motor Type: Brushless Capacity: Bolt: M10 - M20 High tension bolt: M10 - M16 Max. torque: Tightening: 345Nm Nut Busting Torque: 600Nm Square Drive: 12.7mm (1/2") No load speed: High mode: 0 - 2,800 (min-1) Medium mode: 0 - 2,400 (min-1) Low mode: 0 - 1,200 (min-1) Single mode: 0 - 1,800 (min-1) Full load impact rate: 0 - 4,000 (min-1) Weight: 2.0kg (with BSL36A18 battery) Length: 144mm Battery type: BSL36A18 : Li-ion MultiVolt (Battery A) Nut Busting Torque: 600Nm Square Drive: 12.7mm (1/2") No load speed: High mode: 0 - 2,800 (min-1) Medium mode: 0 - 2,400 (min-1) Low mode: 0 - 1,200 (min-1) Single mode: 0 - 1,800 (min-1) Full load impact rate: 0 - 4,000 (min-1) Weight: 2.0kg (with BSL36A18 battery) Length: 144mm Battery type: BSL36A18 : Li-ion MultiVolt (Battery A)