

FLOW 36, TIMBER FILLING EPOXY RESIN BY FLOW RESINS



SKU	Option	Part #	Price
87433945	Size: 1.5kg	FLOW 36 1.5KG	\$61
87433948	Size: 30kg	FLOW 36 30KG	\$720
87433946	Size: 3kg	FLOW 36 3KG	\$96
87433947	Size: 6kg	FLOW 36 6KG	\$178

Model	
Type	Resin
SKU	87433945
Part Number	FLOW 36 1.5KG
Brand	Flow Resins
Packaging + Shipping	
Shipping Weight (Gross)	1.5 kg



Features

Flow 36 is a 2A:1B (measure by weight) timber filling epoxy used for filling the cracks, voids and holes in timber. It is especially good for making repairs and filling the fine veins throughout a slab of timber and is a popular resin choice for timber flooring and furniture companies. **It can also be used as a laminating epoxy for fibreglass repairs and manufacturing.**

It is important to note that Flow 36 does not contain UV inhibitors and will turn a honey colour overtime especially if exposed to sunlight. If you have large voids and holes in your timber that you are filling with resin and wish to keep clear, we recommend using our Easy Flow (Ultra-Clear Casting Resin) or River Flow (Deep Pour) which



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

contain anti-yellowing properties and have overall, much better UV stability.

Flow 36 is a more cost-effective choice for timber filling projects and river tables that will be pigmented a dark colour such as black or blue to fill larger cracks.

For river tables it can be cast to a maximum thickness of 10mm thick. Anything thicker will need to be cast in multiple layers.

Simple 2A:1B mixing ratio (measure by WEIGHT)

Very low viscosity

Self-releases air bubbles

Great thermal stability and low shrinkage

Low VOCs (low odour)

Very durable and scratch resistant once fully cured