

18V FUEL™ ONE-KEY™ 1/2" CONTROLLED TORQUE IMPACT WRENCH WITH FRICTION RING BARE (TOOL ONLY) M18ONEFIW2FC120 BY MILWAUKEE



SKU	Option	Part #	Price
87434134		M18ONEFIW2FC120	\$1809

Model	
Type	Impact Wrench
SKU	87434134
Part Number	M18ONEFIW2FC120
Barcode	4892210238016
Brand	Milwaukee
Technical - Main	
Anvil Size	1/2"
Drive Type	1/2" Drive
Brushless Motor	✓
Dimensions	
Product Weight (Net Weight)	1.3 kg
Warranty	
Warranty	1 Year
Packaging + Shipping	
Shipping Weight (Gross)	1.3 kg



The M18 FUEL™ Controlled Torque Impact Wrench with TORQUE-SENSE™ provides maximum repeatable torque in a pistol grip impact wrench. TORQUE-SENSE™ torque control overcomes common variances seen on the jobsite, maintaining target torque. This performance is enabled by new to world sensors designed in-house by Milwaukee Tool that feed sophisticated machine learning algorithms. Every trigger pull is recorded, and data can be downloaded for customizable reporting to ensure confident installation. This cordless impact wrench is ideal for utility-scale solar projects, where eliminating the 2-step method on the jobsite can deliver maximum installation speed. Milwaukee offers maximum performance and application speed with FUEL™ technology, enabled by POWERSTATE™ brushless motors, REDLINK PLUS™ tool intelligence, and REDLITHIUM™ battery technology.

Features:

TORQUE-SENSE™ torque control delivers TORQUE REPEATABILITY by utilizing proprietary sensors and machine learning developed algorithms to overcome common jobsite variability.

Simplified setup process via ONE-KEY™ eliminates guess-and-check process to deliver target torque.



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Tool output data is stored and is available for download to create customizable tool reports.

TORQUE-SENSE™ error reduction feature set includes low battery shutoff, double-hit prevention, early trigger release detection, F/R direction lock, programmable LED colors, and torque recheck timer.

Reinforced M18™ battery connection providing improved durability and battery retention over life.

A Compact and ergonomic footprint with lightweight design allowing for easier handling, reducing daily fatigue and improving working in tight application spaces.

User feedback LED light shows OK/NOT OK installation

Enabled with machine learning to maintain +/-15% repeatability by adapting to; battery charge level, battery type, jobsite temperature, different torque ranges, tool age, and inconsistent torque during snug up.

Repeat Torque Range: 68-203Nm (50-150 ft.lb).

Supplied with a 12-Month out-of-box manufacturers torque accuracy certification.

Save completed torque mode training run-downs into your ONE-KEY™ library to broadcast to a fleet of tools with identical model numbers.

Over-the-Air update capable for future mode improvements

Specifications:

Anvil Type: 1/2" Square Drive Friction Ring

Nut Busting Torque: 298 Nm Peak

Fastening Torque: 298 Nm Peak

IPM: 0 - 3,500

RPM: 0 - 2,325

Repeat Torque Range: 68 - 203 Nm

Manufacture Certificate of Calibration included: Yes

Includes:

(1) M18 FUEL™ ONE-KEY™ 1/2" Controlled Mid-Torque Impact Wrench with Friction Ring [M18ONEFIW2FC120]

(1) Belt Clip

(Not Included) Batteries & Charger