

12V CROSS + 4 POINT LASER KIT M12C4PLA301C BY MILWAUKEE



SKU	Option	Part #	Price
87434299		M12C4PLA301C	\$925

Model	
Type	Cross Line Laser
SKU	87434299
Part Number	M12C4PLA301C
Barcode	4892210240361
Brand	Milwaukee
Technical - Main	
Accuracy	± 3.18 mm over 10 m
Water Protection Rating	IP54
Dimensions	
Product Length	149 mm
Product Width	81 mm
Product Height	170 mm
Warranty	
Warranty	3 Years
Packaging + Shipping	
Shipping Weight (Gross)	3.8 kg

Our M12™ Green Cross Line & 4-Points Laser provides all-day runtime and the best visibility in its class. Using our M12™ REDLITHIUM™ -ION 3.0Ah Compact Battery (M12B3 sold separately), users get 9+ hours of continuous runtime for ultimate productivity. The high-intensity green laser offers our users superior visibility up to 38 Meters for long-range applications. The vertical and horizontal lines make alignment and level applications easy for our users, while the additional 4-points allow for quick transfers from floor to ceiling and squaring applications. The integrated magnetic bracket features micro-control and pivots on the plumb point for easy and fast alignment. The amplified rare earth magnets provide a stronghold and will not slide on steel studs, while an integrated hang hole makes setup easy and efficient in any environment. As part of the industry-leading M12™ System, our laser is compatible with all M12™ Batteries.

Features

- All Day Runtime - 9+ Hours
- Brightest Green Laser Optimized for Distance
- Micro Control - Pivots on Point
- Vertical & horizontal lines plus 4-points to level, align, plumb and square.
- 38 Meter Working Range
- 50 Meters Range with Detector
- Accuracy: ± 3.18 mm over 10 m
- Amplified Rare Earth Magnets - Will Not Slide on Steel Studs



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

210 Degree Horizontal Fan Angle, 165 Degree Vertical Fan Angle

50mm Plumb Point Access

Self Leveling: +/- 4° Tilt

IP54 Rated: Water and Dust Resistant

1m Impact Resistance

1/4 - 20 & 5/8-11 Thread Mount

3 Year Tool Warranty

Specifications

IP Ratings: IP54

Number of Beams: Vertical & horizontal lines plus 4-points to level, align, plumb and square

Self-Levelling: ± 4° Tilt

Accuracy: ± 3.18mm over 10m

Impact Resistant: 1m

Working Range: 38m

Range with Detector: 50m

Thread Mount: 1/4"-20, 5/8"-11

Includes

M12™ Cross + 4 Points Laser (Tool Only)

M12™ REDLITHIUM™ 3.0Ah Compact Battery

M12™ Lithium-ion Battery Charger

Laser Track Clip with Quick Connect Laser Target